

Attachment "B"

Information required with application to drill, in compliance with NTL-6 effective 7-1-80.

1. Geologic name of surface location:

Red Beds

2. Estimated tops of Important Geological markers:

<u>Tops</u>	<u>Depth</u>
Red Beds	Surface
Rustler	1,270'
Base of the Salt	4,820'
Delaware	5,215'
Bone Spring	9,020'
Wolf Camp	11,890'
Strawn	13,000'
Atokou	13,380'
Marrow	14,180'
Base of Morrow	15,000'

3. Estimated depths of water, oil, gas of other mineral bearing formation:

14,180' Gas in Morrow Formation.

4. Proposed Casing Program, including the size, grade and weight per foot of each string and whether new or used.

See Application -9-331-C

5. See "BOP sketch" attached.

6. See "Mud Program" attached.

7. List of Auxillary Equipment to be used:

1. Kelly Cock
2. Flow show indicator
3. Pit level indicator
4. Full opening valve on floor for drill pipe being used (Inside BOP)
5. Gas Detector
6. Geolograph
7. Mud loggers will be location while drilling objective sands.
8. Mud gas separator
9. De-Gasser
10. De-Sander
11. De-Silter

8. Possible DSTs:

Bone Spring = 10,200'
Atokou = 13,500'

Logs: GR-Sonnic, DLL, Newtron Density
(No cores anticipated)