

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

LEASE

NM 2593

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ gas ☐ other ☒ Dry Hole  
well well2. NAME OF OPERATOR  
Blanks Energy Corporation3. ADDRESS OF OPERATOR  
600 Blanks Bldg., Midland, Texas 797014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: TD @ 10,823' PBTD 3805'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

☐ TEST WATER SHUT-OFF  
☐ FRACTURE TREAT  
☐ SHOOT OR ACIDIZE  
☐ REPAIR WELL  
☐ PULL OR ALTER CASING  
☐ MULTIPLE COMPLETE  
☐ CHANGE ZONES  
☐ ABANDON\*  
☐ (other)

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWell, NEW MEXICO

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Roberts-Yates9. WELL NO.  
110. FIELD OR WILDCAT NAME  
Undesignated Dublin Ellenburger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T-26-S, R-38-E

12. COUNTY OR PARISH

Lea New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2986' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 7/21/81 Spotted 25 sx plug of class "C" cement @ 1880' (Note: Left fish in hole @ 1950'. 70' tbg. w/pkr.)
- 7/22/81 Lost plug, spotted 100 sx class "C" @ 1880'.
- 7/23/81 Tagged plug @ 1460'. Shot off csg. @ 1317'. Spotted 150 sx class "C" cement w/2% CaCl<sub>2</sub> @ 1393'.
- 7/24/81 TOC 1210'. Spotted 125 sx class "C" w/2# Flocel/sk & 2% CaCl<sub>2</sub> @ 450'. Could not tag plug. Spotted 100 sx class "C" w/2# Flocel/sk & 2% CaCl<sub>2</sub> @ 450'.
- 7/25/81 TOC @ 453'. Set plug @ 453' w/100 sx class "C" w/2# Flocel/sk & 2% CaCl<sub>2</sub>. TOC @ 350'. Spotted 50 sx class "C" @ surface. Set marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Tim Fardley TITLE Engineer DATE August 17, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED  
AUG 14 1986  
O.C.D.  
HCBBS OFFICE