

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other ☒ Dry Hole

2. NAME OF OPERATOR
Blanks Energy Corporation

3. ADDRESS OF OPERATOR
600 Blanks Bldg. Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See Mexico below.)
AT SURFACE: 1980' FNL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☒
☐
☐
☐
☐
☐

(other) Plug back @ zone Comp.

5. LEASE

NM-2593

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Roberts-Yates #1

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Undesignated Dublin Ellengurger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 19, T-26-S, R-38-E

12. COUNTY OR PARISH
Lea County

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
2986' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/25/80 - Reached T.D. of 10823'.

11/26/80 - Logging, WIH w/bit to work through "tite" spot.

11/27/80 - stk DP @ 10700'. Jarred on pipe.

11/28/80 - Backed off @ 10562' left bit, reamer, stabilizer & 4 DC's in hole.

11/29/80 - Finished logging.

11/30/80 - Spotted 66 sk plug @ 10255'. 37 sk plug @ 8630', 37 sk plug @ 6732', 39 sk plug @ 5391', 110 sk plug @ 4130', 45 sk plug @ 3937'. (All CMT is class "H".)

12/2/80 - Dressed off plug to 3805'.

1/14/81 - MI @ RU PU. Attempt to complete in the Queen zone.

1/16/81 - Spotted 250 gals 15% DS-30 over open hole interval 3707-3805. BDP 1500#, avg TP 1000#, Mx TP 1500#, ISIP 1200#

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE _____

DATE _____

Approved for Release

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE *Karen E. Payne*

DATE *2-23-81*

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐☐FRACTURE TREAT ☐☐SHOOT OR ACIDIZE ☐☒REPAIR WELL ☐☐PULL OR ALTER CASING ☐☐MULTIPLE COMPLETE ☐☐CHANGE ZONES ☐☐ABANDON* ☐☐(other) Plug back ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/19/81 - Swbd load back w/trace oil and very slight show of gas.

1/21/81 - Acidized w/2000 gal 15% DS-30. Mx TP 1825# ISIP 1500#.

1/23/81 - Swbd load back w/trace oil, 5 BLW & SA, attempt to POH w/pkr Stk @ 3230'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Gay First

TITLE

Engineer

DATE

2-13-81

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Page 2 of 2

*See Instructions on Reverse Side

RECEIVED

MAR 3 1981

CLARK, ALBERT