

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐

2. NAME OF OPERATOR  
Blanks Energy Corp.

3. ADDRESS OF OPERATOR  
600 Blanks Bldg., Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION OF WELL, SURFACE, AND DEPTH OF WELL BELOW.)  
AT SURFACE: 1980' FNL @ 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM-2593  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD OR WILDCAT NAME

Undesignated Dublin Ellenburger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 19, T-26-S, R-38-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2986' G. L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Displace hole w/mud laden fluid.
2. Spot 150' cmt plug (40 sx Class "C") across 8 5/8" csg shoe (3650'-3800'. Shoe @ 3707') See attached well diagram. (Note: pkr stk @ 3230', will attempt to POH, if unable to, will spot 50' of Class "C" on top of it.)
3. Cut-off 8 5/8" csg @ approx 1300'. POH and LD csg. Spot 200' cmt plug (77 sx Class "C") across cut (1200'-1400').
4. Spot 100' plug (56 sx Class "C") across 13 3/8" csg shoe (350-450' shoe @ 400').
5. Spot 15 sx plug (Class "C") @ surface.
6. The location will then be levelled, cleared of junk, marked

\* and identified as per rule 202 of the NMOCC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Engineer DATE 2-12-81

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEER DATE FEB 24 1981  
CONDITIONS OF APPROVAL, IF ANY:

\* (Note: Above recommendation was given by Mr. Pete Chester of the USGS via telephone 2-12-81.)

\*See Instructions on Reverse Side