

ELEVATIONS:
G.L. 2986'
KB - 2999'

1330' ENE + 1230' ENL OF SECTION
13 T. 41 N. R. 33 E., LEA COUNTY
NEW MEXICO

400' - 13 3/8" TC # 5T+C

CMTD W/4203K CLC" W/1/2 C&C/2
CIRC 353K TO PIT

SPUNDED: CABLE TOOL 9-15-80

SPUNDED: KOTNEY 10-4-80

CSG PT: 11-29-80

TOC: 490'

DT TOOL 2 2100'

CMTD 2ND STAGE W/4003K HONED
LIFE W/1/2 SALT/13K 1/4# FLO/ELE/1K
+ 1/2# GILSONITE/1K THREADED IN
W/1003K CLASS C "NEET" NO RETURNS

2 1/8" #7 #5-65
BRELIE TOOL

3230' PKR STUCK

3670' T-QUEEN

3707' - 8 1/8" (1850' 3532' 1807' 0624#) STAL
CMTD 1" STINE W/4003K HONED LIFE
W/1/2 SALT/1K 5 1/2# GILSONITE/1K +
1/4# FLO/ELE/1K THREADED IN W/5003K
CLASS C "1/4" # FLO/ELE/1K.

7 7/8" OPEN HOLE

PBTD 3805'

2 1/8" #7 #5-65
BRELIE TOOL
3670' T-QUEEN
3707' - 8 1/8" (1850' 3532' 1807' 0624#) STAL

T.D. 10363'

PLUGS:
453K & 3937'
1103K & 4130'
393K & 5391'
273K & 6732'
373K & 8433'
603K & 10255'

NOTE LEFT
FIG. 1 IN HOLE
210362'
REARER
STABILIZER
BIT 121T SUB
+ F.O.C.S.