

COPY TO O. G. C.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instruction. on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 2244

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Samedan-Hughes Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Jalmat (Gas)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASection 19, T-23-S,
R-37-E, NMPM

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Doyle Hartman

3. ADDRESS OF OPERATOR

P. O. Box 10426, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 1980 FNL & 660 FWL (E)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3337.8 G.L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud Notice and Set Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded well at 11:00 p.m. CDT 10-13-80. Drilled well to a total depth of 455'. Ran 12 joints (456') of 8 5/8 OD, 23 lb/ft, ST&C casing and landed at 453' RKB. Cemented with 150 sx of Class C cement containing 4% gel, 1/4 lb/sx floreal and 2% CaCl followed by 150 sx of Class C cement containing 2% CaCl and 1/4 lb/sx floreal. Circulated 80 sx of excess cement to pit. Plug down at 10:30 a.m. CDT 10-14-80. WOC 18 hours. Pressure tested casing to 700 psi. Pressure held okay.

RECEIVED

OCT 16 1980

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Michelle Hernandez

TITLE Administrative Assistant

DATE 10-15-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

OCT 21 1980

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side