

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 300252710160
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name T. M. LANKFORD WN
8. Well No. 2
9. Pool name or Wildcat LANGLIE MATTIX 7RQn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator ARCO OIL AND GAS COMPANY
3. Address of Operator BOX 1710, HOBBS, NEW MEXICO 88240	4. Well Location Unit Letter F : 1980 Feet From The NORTH Line and 1980 Feet From The WEST Line Section 25 Township 23S Range 36E NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3341.8' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☒ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TA & HOLD WELL BORE FOR FUTURE USE
TD 3730', PBD 3667', PERFS 3442-3648'

Procedures as follows:

1. MIRU DDPV
2. Give NMOCD 24 hr notification of pressure test on csg
3. Install BOP & POH w/tbg & ACC
4. RIH w/CIBP on tbg
5. Set CIBP @ $\pm 3430'$
6. POH w/l jt
7. Circulate with 8.6# brine and co-rosion inhibitor
8. SI Rams on BOP & press test to 500#. Install chart
9. If csg holds, POH, laying tbg down. Leave 1 jt on flange
10. RDCL. Close all tbg, csg, surface csg valves

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James D. Cogburn TITLE Services Supervisor DATE 8-18-89
TYPE OR PRINT NAME James D. Cogburn TELEPHONE NO. 392-3551

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR TITLE DATE AUG 21 1989

CONDITIONS OF APPROVAL, IF ANY: