

5-USGS-Hobbs

1-R.W. Blohm-Midland

1-Conoco-Hobbs

1-W.A. Frnka-Tulsa

1-File

1-Conoco-Midland

Form 9-331
Dec. 1973

1-J.Mic., Engr.

Form Approved.
Budget Bureau No. 42-R1424

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐2. NAME OF OPERATOR
GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. Box 730, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Ltr. G, 1650' FNL
AT TOP PROD. INTERVAL: & 1980' FEL
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 CHANGE ZONES ☐
 ABANDON* ☐
 (other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
DEC 22 1980

U. S. GEOLOGICAL SURVEY
 HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE	NM-02969-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	--
7. UNIT AGREEMENT NAME	--
8. FARM OR LEASE NAME	Federal "33"
9. WELL NO.	1
10. FIELD OR WILDCAT NAME	Unesignated Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Sec. 33, T-26-S, R-33-E
12. COUNTY OR PARISH	Lea
13. STATE	New Mexico
14. API NO.	--
15. ELEVATIONS (SHOW DF, KDB, AND WD)	3227.6 G.L.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/10/80 Ran and set 112 jts. 9 5/8" 36# N80 and 36# K-55 8r ST&C R-3 Cond. "A" Casing and set at 4900'. (35 jts. N-80-1550' and 77 jts. K-55-3325'). Halliburton cemented w/5000 sxs. Lite, 15# salt, 1/4# Flocele, 5# Gilsonite/sx. Tailed in w/200 sxs. Class "C" cement. Total cement 5200 sxs. Plug down at 1:00 P.M. Circulated 250 sxs. WOC.

12/11/80 Waited on cement 18 hrs. Pressured to 1200# on casing for 30 minutes. OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Supt. DATE 12/16/80

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

DEC 22 1980

U. S. GEOLOGICAL SURVEY
 ROSWELL, NEW MEXICO

See Instructions on Reverse Side