

5-USGS-Hobbs

1-R.W. Blohm-Midland 1-Conoco-Midland

1-W.A. Frnka-Tulsa

1-File

Form 9-331
Dec. 1973

1-J.Mic., Engr.

1-Conoco-Hobbs

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
Getty Oil Company3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit Ltr. G, 1650' FNL &
AT TOP PROD. INTERVAL: 1980' FEL
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐☐
☐
☐
☐
☐
☐
☐
☐

(other) Commence drilling operations

5. LEASE

NM-02965-(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "33"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33, T-26-S, R-33-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3227.6 G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/23/80 Sharp Drilling Company spued 17 1/2" hole at 7:00 A.M. 13 3/8"

11/29/80 Drilled 17 1/2" hole to 805'. Ran 25 jts. (778') of 15 3/8" OD H-40 48# 8rd ST&C R-3 and set at 805'. Halliburton cemented w/700 sxs. Class C cement w/1/4# Flocele, 6% Gel, and 2% CaCl. Tailed in w/200 sxs. Class C cement w/1/4# Flocele and 2% CaCl. Total cement: 900 sxs. Plug down at 1:45 A.M. Circulated 250 sxs.

11/30/80 Waited on cement 18 hrs. tested casing to 600# for 30 minutes. OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 12/3/80

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

DEC 5 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side