

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐
well well other

2. NAME OF OPERATOR

Equitable Petroleum Corporation

3. ADDRESS OF OPERATOR

P.O. Box 8407, Metairie, La. 70011

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

☐

☐

☐

☐

☒

☐

☐

☐

5. LEASE

NM-19447

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Exxon Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

East Mason - Delaware Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8 - 26S-32E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3201 DF; 3202 KDB; 3193 GI

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. changed on recommendation of on site geologist. Well was drilled to 4410' and 4½" casing was cemented at 4399' with 50 sks. Class "C" cement. Base of salt section is at 4370'. Moved out rotary rig 7-8-81. Moved in completion rig 7-25-81 with Reverse Unit and drilled to T.D. of 4425'. Changing of rigs allowed better control over drilling depth. 4½" 10.5# K-55 ST&C casing substituted for 5½" casing because of availability.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donald Gilbert TITLE Production Mgr. DATE 8-21-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

AUG 26 1981

*See Instructions on Reverse Side