

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Amoco Production Company
3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL X 1980' FEL, Sec. 6  
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4)  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

MAY 19 1981

U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

5. LEASE  
NM-13647
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Perro Grande Unit
8. FARM OR LEASE NAME  
Perro Grande Unit
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Wildcat Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
6-26-35
12. COUNTY OR PARISH  
Lea
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3279.6' GL

Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 4-13-81 Abbott Bros. (Rig#5) moved out and MGF Drilling Co. (Rig #5) moved on 4-14-81. Started reaming a 26" hole 11:00 a.m. 4-19-81. Drilled to a TD 1021'. Ran 991' 20" 133# K-55 casing and set at 1017'. Cemented with 1320 sacks Lite and 450 sacks Class C. Plug down 1:45 a.m. 4-24-81. Circulated 85 sacks. Tested casing to 600 psi for 30 min. and OK. Reduced hole to 17-1/2" and resumed drilling.

0+4-NMOCD, H 1-Hou 1-Susp 1-W. Stafford, Hou 1-GPM

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Greg Mitchell TITLE Admin. Analyst DATE 5-7-81

APPROVED BY \_\_\_\_\_ (This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

ROGER A. CHAPMAN

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

MAY 21 1981

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side  
ROSWELL, NEW MEXICO