STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

	_
NO. OF CUPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPENATOR	

OIL CONSERVATION DIVISION

Form C-103 .

DISTRIBUTION	P. O. BOX 2088	Revised 10-1-78
SANTA FE	SANTA FE, NEW MEXICO 87501	•
FILE		5a, Indicate Type of Lease
U.S.G.S.	4	State Foo X
LAND OFFICE		5. State Oil & Gas Lease No.
OPERATOR	J	
		mmmmmm -
SUNDR	RY NOTICES AND REPORTS ON WELLS	
(DO HOT USE THIS FORM FOR PRO USE "APPLICAT	OPOSALS TO ORILE OR TO DEEPEN ON PLUG BACK TO A DIFFERENT RESERVOI FION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	
1.		7, Unit Agreement Name
OIL GAS WELL X	OTHER.	
2. Name of Operator		8. Farm of Lease Name
Coquina Oil Corporati	on ·	Buckeye
3. Address of Operator		9. Weil No.
P. O. Drawer 2960, Mi	dland, Texas 79702]
4. Location of Well		10. Field and Pool, or Wildcat
ſ	660 FEET FROM THE North LINE AND 1980	Undes. Antelope Ridge
UNIT LETTER	FEET FROM THE LINE AND	THITTING THE
Wost	15 TOWNSHIP 24S RANGE 34E	
THE WEST LINE, SECTI	ION TOWNSHIP 240 RANGE	NMPM. {
- manifer and the same of the	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	((((((((((((((((((((
	3516' GL	Lea (\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
The Check	Appropriate Box To Indicate Nature of Notice, Repo	ort or Other Data
	· · ·	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
TEMPORARILY ABANDON	[]	
PULL OR ALTER CASING	<u> </u>	
	OTHER	
OTHER		
13 Describe Proposed or Completed O	operations (Clearly state all pertinent details, and give pertinent dates	s, including estimated date of starting any proposed
work) SEE RULE 1103.	, , , , , , , , , , , , , , , , , , , ,	•
Well was drilled to a	TD of 15,300'. Cement plugs were set @ 1	3,985-14,500'310 sacks;
12,500-12,600'50 sa	cks. Additionally, spotted cmt plugs as f	ollows:
12,433-12,333'	50 sx Class H w/0.1% HR-5	
9,488- 9,388'	50 sx Class H Neat	•
3,100 3,000		
Cut off 9-5/8" casing	, @ 5017'. Pull & LD casing. Spot cmt plu	qs as follows:
cat off 5 5/6 casting	(001) . Vall a 25 000 (11) . They are pro-	3 , - ,
5,062-4,987'	100 sx Class C Neat	
1,700-1,600'	50 sx Class C Neat	
500-400'	50 sx Class C Neat	
500-400	50 SX Class C Near	
6 1 - 56 1 - 1 - 1 - 1	answer level Cook 10 and confine plus	nd install dry holo markor
cut off casing below	ground level. Spot 10 sack surface plug a	nd mstall dry note marker.
Well P & A'd 4/15/82.		
18. I hereby certify that the information	n above is true and complete to the best of my knowledge and belief.	
	•	
R'OL M D.	by Drilling Manager	OATE April 19, 1982
SIGHED JULY 111. 1 AND	•	
7	C) A F	COTOR JAN $11\ 1983$
Kan Id In	Tille OIL & GAS INDIA	J. 111 X = 1000
APPROVED BY JO RANGE 111	OIL & GAS INSPE	DATE
CONDITIONS OF APPROVAL, IF ANY	VI APT 30-025-271	<i>57</i> 分
	· /// + / 0 0 1 1	