| Form 9-331 Dec. 1973  UNITED STATES 11. 11. 11. 12. 12. 12. 12. 12. 12. 12.  | <b>HOIS</b> EH  |
|--|---|
| Form 9–331 Dec. 1973   | Form Approved. Budget Bureau No. 42-R1424   |
| UNITED STATES N. M. 120 MEXI   | O5. CEASE NM 29694  |
| UNITED STATES #, # CONTROL OF THE INTERIOR OF  | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME  |
| GEOLOGICAL SURVET  |   |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)   | 7. UNIT AGREEMENT NAME  |
|  | 8. FARM OR LEASE NAME Exxon "A" Federal   |
| 1. oil gas other   | 9. WELL NO.   |
| 2. NAME OF OPERATOR Fraser Industries, Inc.  | 2 10. FIELD OR WILDCAT NAME   |
| 3. ADDRESS OF OPERATOR   | Double "X" Delaware   |
| P.O.Box 6099 Big Spring, Tx. 79720   | 11. SEC., T., R., M., OR BLK. AND SURVEY OR   |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)   | AREA Sec. 23-24S-32E  |
| AT SURFACE:1650' FNL & 330' FWL  | 12. COUNTY OR PARISH 13. STATE  |
| AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same   | Lea N.M.  |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  | to B. A. Landing and Control of the |
| REPORT, OR OTHER DATA  | 15. ELEVATIONS (SHOW DF, KDB, AND WD)   |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:   | 3598.6' GL.   |
| TEST WATER SHUT-OFF  FRACTURE TREAT  Cementing 8 5   | 5/8" Csg.   |
| SHOOT OR ACIDIZE   |   |
| REPAIR WELL USE PULL OR ALTER CASING TO TO THE TOTAL TO T | (NOTE: Report results of multiple completion or zone change on Form 9-330.)   |
| MULTIPLE COMPLETE  |   |
| CHANGE ZONES   ABANDONS  |   |
| ABANDON* [] [] (other)   |   |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent  | firectionally drilled, give subsurface locations and  |
| 6-8-82 The above well spudded.   |   |
| 6-10-82 8 $5/8$ " Csg. set at $1103$ ' & 0 to drilling pits.   | Cmt. w/500 sks circ. cemt. returns  |
| 6-17-82 4 1/2" Csg. set at 5013' and   | U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO  |
| Subsurface Safety Valve: Manu. and Type  | Set @ Ft.   |
| 18. I hereby certify that the foregoing is true and correct  |   |
| SIGNED Polly Sancaster TITLE Accountant  | DATE6-29-82   |
| (Qrig. Sgd.) GEORGE H. STEWTH pace for Federal or State of   | fice use)   |

RECEIVED

JUL 26 1982

HOBBS OFFICE