

Form 9-331
Dec. 1973

N. M. OIL CONS. COMMISSION
P. O. BOX 1983

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES HOBBS, NEW MEXICO 88240
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 890' FNL & 990' FEL
AT TOP PROD. INTERVAL: ✓
AT TOTAL DEPTH: ✓
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
LC-030556 (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
East Hooper Abo Unit
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Undesignated Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 24, T 32, R 36 E
12. COUNTY OR PARISH: 13. STATE
Lea NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-333b.) 7 1982

RECEIVED

U.S. GEOLOGICAL SURVEY
ROCKY MOUNTAIN DIVISION
DENVER, COLORADO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to plug and abandon the subject well. The procedure with the proposed plugs are as follows:
G-IH W/ open ended drill pipe. Set the following cement plugs w/ class H cement: 7885'-7735' (150', 63sx), 7540'-7390' (150', 63sx), 7100'-6950' (210', 74sx), 6710'-6550' (110', 67sx), 4350'-4250' (100', 42sx), 4042'-3942' (100', 33sx - casing shoe), 1360'-1260' (100', 26sx - Top of salt), and 63', 25sx surface plug. Erect dry hole marker. Vertical approval per George Stewart on 12-10-82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. G. [Signature] TITLE Administrative Supervisor DATE 12-13-82

(This space for Federal or State office use)

APPROVED BY DAVID R. GLASS TITLE _____ DATE _____
CONDITIONS OF APPROVAL IN ANY 1983

For JAMES A. GRHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side