

|                 |  |  |
|-----------------|--|--|
| COPIES RECEIVED |  |  |
| TRIBUTION       |  |  |
| FE              |  |  |
| FILE            |  |  |
| U.S.G.S.        |  |  |
| LAND OFFICE     |  |  |
| OPERATOR        |  |  |

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

|   |  |
|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>  | 7. Unit Agreement Name                           |
| 2. Name of Operator<br>Kern Co.   | 8. Farm or Lease Name<br>Eunice Cooper           |
| 3. Address of Operator<br>250 Mid America Bldg., Midland, Texas 79701   | 9. Well No.<br>2                                 |
| 4. Location of Well<br>UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM<br>THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>24-S</u> RANGE <u>36-E</u> NMPM. | 10. Field and Pool, or Wildcat<br>Langlie-Mattix |
| 15. Elevation (Show whether DF, RT, GR, etc.)<br>Ground Level 3356  | 12. County<br>Lea                                |

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ OTHER ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOBS ☒ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 9-18-82 Spud 12 1/4" hole @ 5 pm 9-17-82. Frilled to 538' in redbeds. Ran 13 joints 20# 8 5/8" H 40 casing and cemented at 538' with 375 sx Class C cement. Plug down 7:22 am.  
9-18-82  
9-19-82 WOC 12 hrs, TSTD csg. to 500 psig ok. Drilled 7 7/8" hole to 1075' in anhydrite.  
9-20-82 Drilling 7 7/8" hole in anhydrite and salt at 1760'  
9-21-82 Drilling 7 7/8" hole in anhydrite and aslt at 2750'  
9-22-82 Drilling 7 7/8" hole in anhydrite and lime at 3200'  
9-23-82 Drilling 7 7/8" hole in lime and sand at 3428'  
9-24-82 Drilling 7 7/8" hole in lime sand and dolomite at 3738'  
9-25-82 Ran Density Neutron, Forxo logs from 3749' and drilled 7 7/8" hole to 3800' in sand and dolomite.  
9-26-82 Ran 95 joints 4 1/2" 10.5# J-55 casing to 3799' and cemented w 850 sx cement. Tstd casing to 1400 psig ok.  
9-27-82 MORT

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddin W. Bay TITLE Engineer DATE 9/27/82  
APPROVED BY Eddin W. Bay TITLE OIL & GAS INSPECTOR DATE SEP 29 1982  
CONDITIONS OF APPROVAL, IF ANY: