

N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) TD, production csg.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

MINERAL SERVICE
ROSWELL, NEW MEXICO

5. LEASE
LC-062749 (C)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Thompson Fed 18 & 2d.
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
East Mason Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-26S, R-32E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 4600' on 11/15/82. Ran 5 1/2", 17 #, K-55 csg set at 4600'. Cmt'd. in 2 stages. 1st stage: 250sx Class C plus 18% salt, tail w/ 166sx Class C w/ 2% CaCl₂. 2nd stage: 408sx Class C w/ 18% salt, 91sx Class C w/ 2% CaCl₂. Circulate 15sx to surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. E. B. [Signature] TITLE Administrative Supervisor DATE Nov 18, 1982

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. [Signature]

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL NOV 24 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side