

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER- <input type="checkbox"/>
Name of Operator JACK HUFF		
Address of Operator BOX 471 MIDLAND, TEXAS		
Location of Well UNIT LETTER <u>G</u> <u>544</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>1980</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>32</u> TOWNSHIP <u>26-S</u> RANGE <u>37-E</u> NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name SHEARN-STATE
9. Well No. 1
10. Field and Pool, or Wildcat SCARBOROUGH YATES 7-R
12. County LEA

15. Elevation (Show whether DF, RT, GR, etc.)
2944.6 GLCheck Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
ALTER OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Finished running 1199' of 23# 8 5/8" surface casing (including one 24# wear joint on top) set at 1209' in anhydrite (one foot below ground level). Ran notched Texas pattern shoe and one centralizer at the top of the first joint.

Geofrac pumped 250 sx. class "C" cement with 8% gel and 1/4# Flocele/sk, 100sx. Class "C" cement with 2% CuCl₂. Displaced with 74bbbls, circulated 138sx. Completed displacement. Waited on cement for 18 hrs. Pressure tested 8-5/8" casing to 1000 p.s.i. for 30 min.

Casing held.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature: [Signature] TITLE Superintendent DATE 11-22-82

ORIGINAL SIGNED BY
JERRY SEXTON
DISTRICT 1 SUPR.
DATE NOV 24 1982

COPIES OF APPROVAL, IF ANY:

RECEIVED

NOV 23 1982

U.S. DEPT. OF JUSTICE
HONORS OFFICE