

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIORS
GEOLOGICAL SURVEY
SUBMIT IN TRIPPLICATE
(Original, Copy, and Duplicate)
HOBBBS, NEW MEXICO 88240
PRO BOX 1980

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR HNG OIL COMPANY	8. FARM OR LEASE NAME Madera 33 Federal Com.
3. ADDRESS OF OPERATOR P. O. Box 2267, Midland, Texas 79702	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FWL & 2310' FNL	10. FIELD AND POOL, OR WILDCAT Pitchfork Ranch Morrow
14. PERMIT NO. -	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3427' GR
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T24S, R34E
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) casing test & Cement job.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

2-18-83 - Spud at 6:00 p.m.

2-19-83 - Set 613 feet of 13-3/8" 48# H-40. Cemented with 250 sacks pacesetter lite and 250 sacks Class C, circulated to surface. 30 minutes pressure tested to 1500#. WOC - 18 hours.

2-27-83 - Set 5191 feet of 9-5/8" K-55, 40# & 36#. Cemented with 2500 sacks pacesetter lite and 475 sacks Class C, circulated to surface. 30 minutes pressure tested to 2000#. WOC - 22-1/2 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty Seldon

TITLE

Regulatory Acalyst

DATE

3/17/83

(This space for Federal or State office use)

APPROVED BY

(ORIG. SGD.) DAVID R. GLASS

DATE

CONDITIONS OF APPROVAL, IF ANY

MAR 23 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

MAR 29 1983

REC.
HOBBS OFFICE