

N. M. OIL CONS. COMMISSION

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

P. O. BOX 1980

HOBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR Robert E. Landreth

3. ADDRESS OF OPERATOR Energy Square, Suite 507
505 N. Big Spring, Midland, Texas 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL of Section 29
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED

MAY 9 1983

OIL & GAS

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
NM 14338

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Gulf 29 Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 29, T-24-S, R-35-E

12. COUNTY OR PARISH Lea 13. STATE
New Mexico

14. API NO.

30-025-28171

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3325' KDB

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was plugged and abandoned according to our procedure submitted on April 5, 1983, approved April 21, 1983 as follows:

1. Spotted 30 sx. cement from 5325' to 5436'.
2. Spotted 30 sx. cement from 1800' to 1900'.
3. Spotted 30 sx. cement across base of 8-5/8" casing from 410' to 310'.
4. Spotted 10 sx. cement at surface.

10.1 pound per gallon mud was used between plugs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert E. Landreth TITLE Owner DATE 5/3/83

APPROVED BY _____ (This space for Federal or State office use)

APPROVED BY Lee H. Hester TITLE _____ DATE 8-13-85

CONDITIONS OF APPROVAL, IF ANY: