

**N. M. OIL CONS. COMMISSION**  
**P. O. BOX 1980**  
**HOBBS, NEW MEXICO 88240**

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
Flagstone Petroleum Corp. c/o Jubilee Energy
3. ADDRESS OF OPERATOR  
3100 N. "A", Bldg. E, Suite 103, Midland, TX
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☒  
FRACTURE TREAT ☒  
SHOOT OR ACIDIZE ☒  
REPAIR WELL ☒  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-31-83 Spud well @ 9:00 p.m.  
9-01-83 Drilled to 31'. Set 13 3/8" 48# casing @ 30' and cemented w/25 sx. Class "C" cement.  
9-02-83 Waiting on rig.  
9-28-83 Drilling resumed. Drilled to 815' and set 9 5/8" 36# casing to 815' and cemented w/300 sx. Circulated 15 bbls. cement.  
10-12-83 Reached TD of 5365'. Ran 5" casing to 5230' and cemented w/200 sx. Class "C" cement.  
10-16-83 Ran 3 1/2" liner to 5365' and cemented w/75 sx. Class "C" cement.  
10-21-83 Perforated from 5284' to 5322'.  
10-22-83 Acidized perforations with 2000 gallons 7 1/2% Hcl.  
10-24-83 Fraced perforations w/20,000 gal. 70 Quality foam + 23,500# sand.  
Inj. rate - 16 bbls/min @ 3800#. SIP 1480#. 10" - 1380#.

Subsurface Safety Valve: Manu. and Type

Set @ . Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE President DATE 11-17-83

**ACCEPTED FOR RECORD**  
**(ORIG. SGD.) DAVID R. GLASS**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL \_\_\_\_\_ DATE \_\_\_\_\_

NOV 28 1983

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

5. LEASE  
NM-19001
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Phillips Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Bradley Delaware (Ext.)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 24, T-26-S, R-33-E
12. COUNTY OR PARISH  
Lea
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW OF, KBT, AND WD)  
3370' G.L.

RECEIVED  
NOV 19 10 26 AM '83  
BUREAU OF LAND MANAGEMENT  
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

RECEIVED  
NOV 29 1983  
O.C.D.  
HOBBS OFFICE