Form	331.	
Dec.	1973	۲.

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON\*

form Approved.

## .....UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1977	Budget Bureau No. 42-R1424	
HORES WITTED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM 19453	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
CONTRACTOR AND DEPORTS ON WELLS	7. UNIT AGREEMENT NAME	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil G gas gr	Federal 53 "COM"	
well well other	9. WELL NO.	
2. NAME OF OPERATOR	1	
Pogo Producing Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Wildcat	
P.O. Box 10340 Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.)	Sec. 17, I-26-S, R-34-E	
AT SURFACE: 1980' FSL & 660' FWL	12. COUNTY OR PARISH 13, STATE	
AT TOTAL DEPTH: 10001 FSL & 6601 FWL	Lea New Mexico	
AT TOTAL DEPTH: 1980' FSL & 660' FWL	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3360.6' GR 3387' KB	
	L.,	

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

(other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

SUBSEQUENT REPORT OF:

8/22/84 - PBTD 13,880' 10 ppg brine, Perf 2 7/8" tbg w/3 holes @ 13,310'-311'. Kill well, cut tbg w/jet cutter @ 13,333'. Ran 5" 18# CIBP & set @ 13,290'. Ran 7 5/8" CIBP & set @ 12,500'. (Witnessed 8/27/84 by BLM) Placed 36' Cl A cmt on CIBP from 12,500'-12,464'. SI well w/csg relief valve open. WO csg pullers.

CONTINUED ON ATTACHED SHEET

Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct  SIGNED and Lillegie Operations  TITLE	Engineer 9/18/84
ACCEPTED FOR RECORD space for Federal or	State office use)
APPROVED BY	DATE

2FL 7 0 13R4