

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
K-3424

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name --
2. Name of Operator MORRIS R. ANTWEIL	8. Farm or Lease Name Gulf State
3. Address of Operator P. O. Box 2010 Hobbs, New Mexico 88241	9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 23S RANGE 37E NMPM.	10. Field and Pool, or Willcat Cline Drinkard-Abo
11. Elevation (Show whether DF, RT, GR, etc.) 3296.4 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 7175' TD. Ran logs. Ran 215 jts. 5 1/2" 15.5# J-55 casing 7196.44' with DV tool at 4316' and 32.79' shoe joint. Cemented in two stages to surface with first stage 500 sx Halliburton Light cement containing 18% salt and 1/4 #/sk Flocele and 350 sx Class "C" with 5 #/sk salt, 1/4 #/sk flocele and 2/10% Halad-9. Circulated 4 hours. Second stage cement consisted of 400 sx Halliburton Light cement with 2% CaCl2 and 100 sx Class "C" with 2% CaCl2. Plug down 9:30 PM 7 Nov 83. Circulated 60 sx cement above DV tool on first stage and 40 sx to surface on second stage. Will drill out DV tool and test casing when completion operations begin.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Hill TITLE Agent DATE 8 Nov 83
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NOV 9 1983