Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

 $f_{-}^{d},$

UNITED STATES

			Du	a Rer Date	:au 110	, 4 2-	K 1 + Z
١	5.	LEASE ,	1				- 3

DEPARTMENT OF THE INTERIOR	Federal NM 16 353			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME			
1. oil	8. FARM OR LEASE NAME Federal "27"			
well well other Dry	9. WELL NO. 1			
2. NAME OF OPERATOR Woods Petroleum Corporation	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Double X			
3555 NW 58th, Suite 500, Okla. City, OK	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Section 27-T24S-R32E			
AT SURFACE: 660 FNL & 660 FWL Sec. 27-24S-32E	12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same	Lea New Mexico			
	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	30-025-27015 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3571.6' Gr.			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3371.0 01.			
TEST WATER SHUT-OFF				
FRACTURE TREAT				
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)			
PULL OR ALTER CASING U U MULTIPLE COMPLETE	change on Form 5-550.)			
CHANGE ZONES				
ABANDON* (other)				
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertined	lirectionally drilled, give subsurface locations and			
On 9/3/80 set cement plugs as follows:				
250' plug 4979-4729' 100' plug 4265-4165'				
150' plug 1335-1185'				
100' plug 1082- 982'				
Used a total of 175 sx Class "C" cement with On 9/4/80"	2% cc.			
Installed 10' surface plug Installed dry hole marker.	Sed 11 1980			
installed dry note marker.	S. C. DLOGICAL SURVEY			
	holius, hav medeo			
Subsurface Safety Valve: Manu. and Type	Set @ Ft.			
18. I hereby certify that the foregoing is true and correct				
SIGNED TITLE Drlg Supt, Mi	d-Contate 9/9/80			
(This space for Federal or State of	ffice use)			
APPROVED BYTITLE	DATE APPROVED			
CONDITIONS OF APPROVAL, IF ANY:				
*See Instructions on Reverse	SEP 8 1982 OG 1 JAMES A. GILLHAM			
	DISTRICT SUPERVISOR			