

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Dry
2. NAME OF OPERATOR  
Woods Petroleum Corporation
3. ADDRESS OF OPERATOR  
3555 NW 58th, Suite 500, Okla. City, OK 73112
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660 FNL & 660 FWL Sec. 27-24S-32E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input checked="" type="checkbox"/>	<input type="checkbox"/>
(other) _____	

5. LEASE  
Federal NM 16 353
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal "27"
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Double X
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 27-T24S-R32E
12. COUNTY OR PARISH  
Lea
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3571.6' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**Propose to plug and abandon as follows:**

250' plug 4979-4729'

100' plug 4265-4165'

150' plug 1335-1135'

100' plug 1032-982'

Use a total of 2 1/2 175 sx Class "C" cement with 2% cc.

Install 10' surface plug

Install dry hole marker.

**RECEIVED**

SEP 11 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Drlg Supt, Mid-Cont DATE 9/9/80

(This space for Federal or State office use)

(Orig. Sd.) GEORGE H. STEWART  
APPROVED BY SEP 18 1980  
CONDITIONS OF APPROVAL, IF ANY:

AGING DISTRICT ENGINEER

SEP 18 1980