

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator HNG OIL COMPANY		8. Farm or Lease Name Moore 34 Com.
3. Address of Operator P. O. Box 2267, Midland, Texas 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>north</u> LINE AND <u>1980</u> FEET FROM THE <u>east</u> LINE, SECTION <u>34</u> TOWNSHIP <u>24S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Pitchfork Ranch (Atoka)
15. Elevation (Show whether DF, RT, GR, etc.) 3401.6' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF: 2/27/84

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-15-84 - Set 13,540 feet of 5-1/2" 17# P-110. Cemented with 760 sacks trinity lite weight 4 gel + 1/4#/Sx flocele, 8/10 of one percent Halad-9, 3/10 of one percent HR-7. 1.82 cubic feet/sack. 12.0 ppg. and 450 sacks Class H cement, 6/10 of one percent Halad 22A, 3/10 of one percent HR-7, 1.18 cubic feet/sack. 15.6 ppg.

30 minutes pressure tested to 2700#. WOC - 22-1/2 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Betty Gordon TITLE Regulatory Analyst DATE 3/20/84

APPROVED BY JERRY SEXTON
DISTRICT SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY:

MAR 21 1984