

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" FORM C-1011 FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator HNG OIL COMPANY		8. Farm or Lease Name Moore 34 Com.
3. Address of Operator P. O. Box 2267, Midland, Texas 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>north</u> LINE AND <u>1980</u> FEET FROM <u>east</u> THE <u>34</u> LINE, SECTION <u>24S</u> TOWNSHIP <u>34E</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Pitchfork Ranch (Atoka)
15. Elevation (Show whether DF, RT, GR, etc.) 3401.6' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-13-84 - Spud 8:30 a.m.

2-14-84 - Set 615 feet of 11-3/4" 47# K-55 ST&C and 42# H-40 ST&C. Cemented with 250 sacks halliburton lite cement 1/4# Flocele 2% CaCl mixed at 12.7 ppg and 165 sacks Class C 2% CaCl mixed at 14.8 ppg. Circulated to surface. WOC - 24 hours. 30 minutes pressure tested to 1500#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Betty Gildon TITLE Regulatory Analyst DATE 2/17/84

APPROVED BY OPINION SIGNED BY JERRY SEXTON  
DISTRICT SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY:

DATE FEB 20 1984