

(May 1983)

UNITED STATES  
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)

Budget Bureau No. 42-R1424.

GEC GICAL SURVEY

5. LEASE DESIGNATION AND SERIAL NO.

NM 21511

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Madera 33 Federal Com.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Pitchfork Ranch /Morrow/

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T24S, R34E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR  
HNG OIL COMPANY

3. ADDRESS OF OPERATOR  
P. O. Box 2267, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

1980' FSL & 1980' FEL, Section 33.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3401.3' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF: 5/25/84

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing test & cement job.

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-7-84 - Set 13,300 feet of 7" 26# P-110. Cemented with 775 sacks TLW & 1/4 #/sx. Flocele + 4% Gel and .8 of 1% Halad-9, 12.0 ppg, and 400 sacks Class H + 2% Potassium Chloride + .6 of 1% Halad-A + .3 of 1% HR-7, 15.6 ppg. 30 minutes pressure tested to 2000#. WOC 20 hours.

6-28-84 - Set 5-1/2" liner at 14,677 feet. Top of liner at 12,989'. (20# S-95). Cemented with 210 sacks of Class H cement + 4/10 of 1% Halad-14 + 1/10 of 1% HR-5, 16.4 ppg. 30 minutes pressure tested to 1500#. WOC - 20-1/2 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty Gildan

TITLE Regulatory Analyst

DATE 7/6/84

(This space for Federal or State Office Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 9 1984

\*See Instructions on Reverse Side

NEW MEXICO