

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
reverse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM20384

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Chevron U.S.A. Inc.

3. ADDRESS OF OPERATOR

P.O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 660' FWL

14. PERMIT NO.

30-025-28651

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3356.6' GL

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson C Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Bradly Bone Springs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 29, T26S, R43E

12. COUNTY OR PARISH 13. STATE

Lea

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

P&A'u well as follows:

10/16/85 Set CIBP @ 9775' and capped with 35' of cement.

10/17/85-10/21/85 Removed 7 5/8" casing from surface to 5500'.

10/22/85-10/25/85 Set cement plugs from:

9427'-9600'	35 sacks
8001'-8070'	130 sacks
7828'-8001'	35 sacks (Tagged)
5170'-5593'	270 sacks (Tagged)
5020'-5170'	75 sacks
1064'-1264'	50 sacks
Surface - 60'	25 sacks

10/26/85 Cut off wellhead, installed dry hole marker.

Location and access road has been cleared and restored as per BLM requirements.

18. I hereby certify that the foregoing is true and correct

SIGNED

P. H. Buley Jr.

TITLE

Division Drilling Manager

DATE

7-8-1986

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

9-3-86

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side