

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-2244

6. IS INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME Langlie Mattix
2. NAME OF OPERATOR Samedan Oil Corporation	"B-4" Penrose Queen Unit
3. ADDRESS OF OPERATOR 600 N. Marienfeld, Suite 320, Midland, Texas, 79701	8. FARM OR LEASE NAME Hughes "B-4"
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1300' ENL & 500' FWL of Section 17	9. WELL NO. 3
10. FIELD AND POOL, OR WILDCAT Langlie Mattix	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17, T-23-S, R-37-E
12. PERMIT NO.	13. COUNTY OR PARISH Lea
14. ELEVATIONS (Show whether EX, RT, GR, etc.) 3324 GR	15. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	DRILL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other) spud & set casing	☐		☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

5-8-84 Spud 12-1/4" hole @ 9:00 p.m. (5-8-84).

5-9-84 Ran 8-5/8" notched guide shoe, auto fill insert float, 3 centralizers and 8 jts 8-5/8" 20# H-40 ST&C casing set at 334'. Cemented with 150 sx Class "C" w/4% gel & 1/4# flocele & 2% cc. Tail in w/150 sx Class "C" w/2% cc + 1/4# flocele. Circulate 60 sx. Plug down at 9:55 a.m. Float held o.k. WOC 12 hrs.

18. I hereby certify that the foregoing is true and correct

SIGNED

Vernon Diamond

TITLE

Division Clerk

DATE

8/24/84

ACCEPTED FOR RECORD

APPROVED BY

SWG

TITLE

DATE

CONDITIONS OF APPROVAL

AUG 30 1984

Calabaz

NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
AUG 31 1933