ENERGY MID MINERALS DEPARTMENT  C CONSERVATION DIVISION	Ì
	Form C-103 -
SANTA FE. SANTA FE, NEW MEXICO 87501	Revised 10-1-7
FILE	Sa. Indicate Type of Lauss
U.S.O.S.	State X Fre
LAND OFFICE	5. State Oll & Gas Luase No.
OPERATOR	
SUNDRY NOTICES AND REPORTS ON WELLS	
(UO NOT USE THIS FRAM FOR PROPOSALS TO DAILL ON TO GEEFIN ON PEUG SACK TO A DIFFLHENT RESERVOIR.  USE "APPLICATION FOR PERMIT =" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Nume
OIL GAS X OTHER-	8. Farm or Lease Ivame
hare of Operator	· ·
Doyle Hartman	J. F. Janda (NCT-G)
1. Address of Operator	2
Post Office Box 10426 Midland, Texas 79702	10. Field and Pool, or Whideat
G 1980 FEET FROM THE NORTH LINE AND 1650 FEET FROM THE NORTH	Jalmat (Gas)
UNIT LETTER G FEET FROM THE LINE AND FEET FR	
THE East LINE, SECTION 24 TOWNSHIP 23S RANGE 36E	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3342.6 G.L.	Lea
Check Appropriate Box To indicate Nature of Notice, Report or C	Other Data
	NT REPORT OF:
PERFORM BEMEDIAL WORK	ALTERING CASING
TEMPORARILY ASAMOON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CABING CHANGE PLANS CASING TEST AND CEMENT JOS X	
OTHER	
OTHER	,
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, include	ing estimated date of starting any proposed
work) SEE RULE 1103.	
Drilled well to a total depth of 3800'. Ran 94 joints (3819') of 26 lb/ft, LT&C casing and landed at 3800'. Cemented with 900 sx cement containing 3% Econolite and 1/2 lb/sx Floseal followed by 50-50 blend of API Class-C cement and Pozmix A containing 18% sallb/sx Floseal. Plug down at 3:15 p.m. CST 12-04-84. Circulated excess cement to pit. Pressure tested casing to 1500 psi and preokay. Released pressure and float held okay.	of Class-C 500 sx of a Lt and 1/2 485 sx of

Administrative Assistant

December 10, 1984

DEC 12 Tesa

CONDUCTIONS OF APPROVAL, IF ANYS