

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Free <input type="checkbox"/>
5. State Oil & Gas Lease No. B-229

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Doyle Hartman	8. Firm or Lease Name J. F. Janda (NCT-G)
Address of Operator Post Office Box 10426 Midland, Texas 79702	9. Well No. 2
Location of well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1650 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 23S RANGE 36E T.M.P.M.	10. Field and Pool, or Whidcat Jalmat (Gas)
11. Elevation (Show whether DF, RT, GR, etc.) 3342.6 G.L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 8:30 p.m. CST 11-25-84. Drilled well to 432'. Ran 11 joints (428.28') of 9-5/8" OD, 40 lb/ft, Grade B casing and landed at 430'. Cemented with 300 sx Class C cement containing 2% CaCl. Plug down at 9:30 a.m. CST 11-26-84. Circulated 10 sx of excess cement to pit. WOC 18 hours. Pressure tested casing to 700 psi. Pressure held okay.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by Michelle Nemler TITLE Administrative Assistant DATE November 27, 1984

ORIGINAL SIGNED BY JERRY SEXTON
PROVED BY DISTRICT SUPERVISOR TITLE _____ DATE NOV 29 1984
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 28 1961

O.C.D.
HONORARY OFFICE