	UNITED STATE DEPARTMENT OF THE	INTERIOR			E	FORM APPROVED OMB No. 1004-0135 Expires January 31, 200		
	BUREAU OF LAND MAN. Y NOTICES AND REPO		15		5. Lease Ser NM 19	rial No. 9861 🗸		
Do not use the	is form for proposals to II. Use Form 3160-3 (AP	odrill or to re-e	enter an		6. If Indian,	Allottee or Tribe Na	ıme	
SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well	Other				8. Well Nar	ne and No.		
2. Name of Operator EOG Resource						ra 33 Fed	. Com.	:3
3a. Address	<b>5</b> , 10.	3b. Phone No.	(include area	code)	9. API Well	25 <b>298</b> 36		
P.O. Box 2267,			)686-3	608		Pool, or Explorator		
4. Location of Well (Footage, Sec.,	/	<i>in)</i>				or Parish, State		
660' FWL & Sec.33-T24S		L			Lea Co	unty, New	Mexico	
	PROPRIATE BOX(ES) T			F NOTICE R				
TYPE OF SUBMISSION				OF ACTION				
	Acidize	Deepen		Production (Star	t/Resume)	Water Shut-Of		
X Notice of Intent	Alter Casing	Fracture Trea		Reclamation		G Well Integrity		_ yi
Subsequent Report	Casing Repair	New Constru		Recomplete		Other		12
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Aba	indon 🖵	Temporarily Ab Water Disposal	andon			NG
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fit determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8"	tionally or recomplete horizont work will be performed or pro- olved operations. If the operati- nal Abandonment Notices shall for final inspection.) NOTE tubing with	ally, give subsurface rovide the Bond No. on results in a multip be filed only after a PERFS 10 ppg br	incations and on file with ble completio all requirement T TO SiW/35 ine, N	d measured and tr BLM/BIA. Requ n or recompletion nts, including recl ET CIBP 'CMT DI ID tree,	ired subsequent in a new intervi- amation, have b APPROX V TOP. NU 500	ns of all pertinent m reports shall be file al, a Form $3160-4$ size even completed, and 50'ABO' 0 psi. BO	arkers and zones. ed within 30 days hall be filed once the operator has NE OPs.	TO CO
Attach the Bond under which the following completion of the invitesting has been completed. Fil determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8 to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spor	tionally or recomplete horizont work will be performed or pro- olved operations. If the operati- nal Abandonment Notices shall for final inspection.) NOTE tubing with " tubing and p of 145,000#. ng @ 12,975'± 50' and spot ree point of "ree point of 2" cut off. 7 7/8" tubing and ot 35sx plug f	ally, give subsurface rovide the Bond No. on results in a multiple filed only after a <b>PERFS</b> 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 FAG nd spot 2 rom 660'	locations an on file with ble completio all requirement <b>ω/35</b> ine, N assen e to p from al loc 0sx pl 0sx pl to 560	d measured and tr BLM/BIA. Requ nor recompletion ET CBP 'CAT D' ID tree, able out oull out 12,950' ck casind Lug (50s: Lug from D'.	ue vertical depti in a new interva amation, have b APPROX V TOP. NU 500 of PBR of PBR to 12, g. Est x below 5,300'	ns of all pertinent m reports shall be file al, a Form 31604 si seen completed, and . 50'ABD' 0 psi. BC . @ 13.007 ., RIH abc 700'. WC imated re and 50sz ro 5,200	arkers and zones. Sed within 30 days hall be filed once i the operator has NE OPS. 7' or 1 cut OC and t ECOVERY x above) 0'(BASE OI ETNT. (	DE A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the invite testing has been completed. Find determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx p hole market	tionally or recomplete horizont work will be performed or pro- olved operations. If the operati- hal Abandonment Notices shall for final inspection.) NOTE tubing with " tubing and p of 145,000#. ng @ 12,975'± 50' and spot free point of 7/8" tubing and 2" cut off. 1 7/8" tubing a of 35sx plug fi olug @ surface . Clean and	ally, give subsurface rovide the Bond No. on results in a multiple filed only after a <b>PERFS</b> 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 FAG nd spot 2 rom 660' . Cut of level loc	locations an on file with ole completio all requirement <b>TOS</b> ine, N assem e to p from al loc 0sx pl to 560 f well cation.	d measured and tr BLM/BIA. Requ n or recompletion is, including recl FT C.BP 'CAT Di ID tree, able out oull out 12,950' ck casing Lug (50s: Lug from D'. Lhead 4'	ue vertical depti in a new interva amation, have b APPROX V TOP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below	ns of all pertinent m reports shall be file al, a Form 3160-4 si seen completed, and 50'ABO' 0 psi. BC 0 13.007 , RIH abo 700'. WC imated re and 50ss ro 5,200 GL. Welc (OVER)	arkers and zones. within 30 days hall be filed once the operator has NE OPS. 7' or d cut OC and t accovery x above) 0'(BASE ON & INT. d on dry	DE A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx p hole marker 14. I hereby certify that the foregoin Name (Printed/Typed)	tionally or recomplete horizont work will be performed or pri- olved operations. If the operati- hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and p of 145,000#. ng @ 12,975'± 50' and spot ree point of 7/8" tubing and 2" cut off. 1 7/8" tubing and 51 and spot ree point of 2" cut off. 1 7/8" tubing and 51 and spot cut off. 1 7/8" tubing and 52 cut off. 1 53 sx plug fill olug @ surface . Clean and	ally, give subsurface rovide the Bond No. on results in a multiple filed only after a PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 AG nd spot 2 rom 660' . Cut of level loc 200' PLNG	<pre>locations am on file with ole completio all requirement I TO S W/35 ine, N assem e to p from al loc 0sx pl to 560 f well cation. APPRoX APPRoX</pre>	d measured and tr BLM/BIA. Requ nor recompletion nor recompletion ET C.BP 'CAT D' ID tree, able out oull out 12,950' ck casino Lug (50s: Lug from D'. Lhead 4'	ue vertical depti in a new intervi amation, have b APPROX V TOP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below	ns of all pertinent m reports shall be file al, a Form 31604 si seen completed, and . 50'ABD' 0 psi. BC @ 13.007 , RIH abd 700'. WC imated re and 50sp ro 5,200 GL. Welc	arkers and zones. within 30 days hall be filed once the operator has NE OPS. 7' or 1 cut OC and t 2C and t 2C and t 2C avery x above) 0'(BASE ON \$INT. d on dry 65)	be A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx p hole marker 14. I hereby certify that the foregoin Name (Printed/Typed)	tionally or recomplete horizont work will be performed or pro- loved operations. If the operation hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and p of 145,000#. Ing @ 12,975'± 50' and spot free point of 7/8" tubing and 2" cut off. 1 7/8" tubing and 51 35 x plug fi olug @ surface . Clean and ag is true and correct * is the Roark **	ally, give subsurface rovide the Bond No. on results in a multiple filed only after i PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 7AG nd spot 2 rom 660' . Cut of level loc 100' PLNG	locations an on file with ole completio all requirement T TO S <sup>i</sup> W/35 ine, N assen e to p from al loc 0sx pl 0sx pl to 560 f well ation APPRoX APPRoX	d measured and tr BLM/BIA. Requ n or recompletion nts, including recl FT C.BP 'CAT Di ID tree, able out oull out 12,950' ck casing Lug (50s: Lug from D'. Lhead 4' 92.0.9' Engineer 7/17/200	ue vertical depti in a new interva amation, have b APPROX V TDP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below +00' (Par co ' (Tach	ns of all pertinent m reports shall be file al, a Form 3160-4 si seen completed, and 50'ABD' 0 psi. BC @ 13.007 , RIH abd 700'. WC imated re and 50sz ro 5,200 GL. Welc (OVER) MG SPRIM	arkers and zones. within 30 days hall be filed once the operator has NE OPS. 7' or 1 cut OC and t 2C and t 2C and t 2C avery x above) 0'(BASE ON \$INT. d on dry 65)	be A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx pr hole marker 14. I hereby certify that the foregoin Name (Printed/Typed) M. Let Signature M. Calculate	tionally or recomplete horizont work will be performed or proved operations. If the operation hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and p of 145,000#. ng @ 12,975'± 50' and spot ree point of 7/8" tubing and 2" cut off. 1 7/8" tubing and 2" cut off. 1 7/8" tubing and bt 35sx plug fi olug @ surface . Clean and mg is true and correct * is the Roark Clean SPACE	ally, give subsurface rovide the Bond No. on results in a multiple filed only after a PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 For FEDERAL FOR FEDERAL	locations an on file with ole completio all requirement T TO S <sup>i</sup> W/35 ine, N assen e to p from al loc 0sx pl 0sx pl to 560 f well ation APPRoX APPRoX	d measured and tr BLM/BIA. Requ n or recompletion nts, including recl FT C.BP 'CAT Di ID tree, able out oull out 12,950' ck casing Lug (50s: Lug from D'. Lhead 4' 92.0.9' Engineer 7/17/200	ue vertical depti in a new interva amation, have b APPROX V TDP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below +00' (Par co ' (Tach	ns of all pertinent m reports shall be file al, a Form 3160-4 si seen completed, and 50'ABD' 0 psi. BC @ 13.007 , RIH abd 700'. WC imated re and 50sz ro 5,200 GL. Welc (OVER) MG SPRIM	arkers and zones. within 30 days hall be filed once the operator has NE OPS. 7' or 1 cut OC and t 2C and t 2C and t 2C avery x above) 0'(BASE ON \$INT. d on dry 65)	DE A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx pr hole marker 14. I hereby certify that the foregoin Name (Printed/Typed) M. Let Signature M. Calculate	tionally or recomplete horizont work will be performed or pro- loved operations. If the operation hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and p of 145,000#. Ing @ 12,975'± 50' and spot free point of 7/8" tubing and 2" cut off. 1 7/8" tubing and 51 35 x plug fi olug @ surface . Clean and ag is true and correct * is the Roark **	ally, give subsurface rovide the Bond No. on results in a multiple filed only after a PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 For FEDERAL FOR FEDERAL	locations an on file with ole completio all requirement T TO S <sup>i</sup> W/35 ine, N assen e to p from al loc 0sx pl 0sx pl to 560 f well ation APPRoX APPRoX	d measured and tr BLM/BIA. Requ n or recompletion nts, including recl ET C.BP 'CAT D' ID tree, able out oull out 12,950' ck casine Lug (50s: Lug from D'. Lhead 4' 92.0.94 Chrom Chr	ue vertical depti in a new interva amation, have b APPROX V TDP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below +00' (Par co ' (Tach	ns of all pertinent m reports shall be file al, a Form 3160-4 si seen completed, and 50'ABD' 0 psi. BC @ 13.007 , RIH abd 700'. WC imated re and 50sz ro 5,200 GL. Welc (OVER) MG SPRIM	arkers and zones. within 30 days hall be filed once the operator has NE OPS. 7' or 1 cut OC and t 2C and t 2C and t 2C avery x above) 0'(BASE ON \$INT. d on dry 65)	DE A SET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx p hole marker 14. I hereby certify that the foregoin Name (Printed/Typed) M. Let Signature M. Calculate Solution (ORIG. Solution)	tionally or recomplete horizont work will be performed or pro- loved operations. If the operati- hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and p of 145,000#. ing @ 12,975'± 50' and spot ree point of 7/8" tubing and 2" cut off. 1 7/8" tubing and 2" cut off. 1 7/8" tubing and bt 35sx plug fi olug @ surface c. Clean and ig is true and correct * ee Roark ** Chear *	ally, give subsurface rovide the Bond No. on results in a multiple filed only after PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 AG nd spot 2 rom 660' . Cut of level loc 200' PLNG CO' PLNG T FOR FEDERAL	locations an on file with ole completio all requirement I TO S <sup>1</sup> W/35 ine, N assen e to p from al loc 0sx pl 0sx pl to 560 f well ation. APPRoX APPROX APPROX Tritle t or	d measured and tr BLM/BIA. Requ n or recompletion nts, including recl ET C.BP 'CAT D' ID tree, able out oull out 12,950' ck casine Lug (50s: Lug from D'. Lhead 4' 92.0.94 Chrom Chr	ue vertical depti in a new interva amation, have b APPROX V TDP. NU 500 of PBR of PBR to 12, g. Est x below 5,300' below +00' (Par co ' (Tach	ns of all pertinent m reports shall be file al, a Form 3160-4 si seen completed, and 50'ABD' 0 psi. BC @ 13.007 , RIH abd 700'. WC imated re and 50sz ro 5,200 GL. Welc (OVER) MG SPRIM	arkers and zones. Advithin 30 days hall be filed once the operator has NE OPS. 7' or 1 cut OC and t acovery x above) 0'(BASE OI ¢INT. d on dry 65)	_
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fi determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx ff hole marker 14. I hereby certify that the foregoin Name (Printed/Typed) M. Le Signature (ORIG. SG Approved by Conditions of approval, if any, are certify that the applicant holds legs which would entitle the applicant to	tionally or recomplete horizont work will be performed or pro- loved operations. If the operati- hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and pof of 145,000#. ng @ 12,975'± 50' and spot ree point of 7/8" tubing and 2" cut off. 1 7/8" tubing and bug @ surface . Clean and ng is true and correct * ee Roark ** Correct THIS SPACE	ally, give subsurface rovide the Bond No. on results in a multiple be filed only after in PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 TAG nd spot 2 rom 660' . Cut of 1evel 100 200' PLNG T FOR FEDERAL 0DA ince does not warran this in the subject le	locations an on file with ole completio all requirement T TO S <sup>1</sup> U/35 ine, N assen e to p from al loc 0sx pl to 560 f well ation APPRoX APPROX APPROX APPROX Title OR STAT	d measured and tr BLM/BIA. Requ n or recompletion for recompletion FT C/BP CAT D ID tree, able out oull out 12,950' ck casing Lug (50s: Lug from D'. Lhead 4' CAT D ID tree, able out oull out 12,950' ck casing Lug from D'. Lhead 4' CAT D ID tree, able out out 12,950' ck casing Lug (50s: Lug from D'. Engineer	ue vertical depti in a new interva mation, have b APPROX NU 500 of PBR of PBR to 12, g. Est x below 5,300' below too' (Ba coo' (TT Tech 2	ate JUL 1	arkers and zones. Ad within 30 days hall be filed once I the operator has NE DPs. 7' or d cut DC and t acovery x above) 0'(BASE OI (EINT. d on dry 520()2	DE ASET CICR
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fit determined that the site is ready <u>PROCEDURE:</u> 1. Load 2-7/8" 2. PU on 2-7/8" to maximum 2-7/8" tubi 3. POH to 12,9 4. Calculate ff 6,500'. 5. RIH with 2- across 5-1/ 6. POH with 2- 7. POH and spot 8. Spot 10sx ff hole marker 14. I hereby certify that the foregoin Name (Printed/Typed) M. Lee Signature (ORIG. SC Approved by Conditions of approval, if any, are	tionally or recomplete horizont work will be performed or pro- loved operations. If the operati- hal Abandonment Notices shall for final inspection.) NOTE tubing with "tubing and pof of 145,000#. ng @ 12,975'± 50' and spot ree point of 7/8" tubing and 2" cut off. 1 7/8" tubing and bug @ surface . Clean and ng is true and correct * ee Roark ** Correct THIS SPACE	ally, give subsurface rovide the Bond No. on results in a multiple be filed only after in PERFS 10 ppg br pull seal If unabl 20sx plug 5-1/2" se d spot 10 TAG nd spot 2 rom 660' . Cut of 1evel 100 200' PLNG T FOR FEDERAL 0DA ince does not warran this in the subject le	locations an on file with ole completio all requirement T TO S <sup>1</sup> U/35 ine, N assen e to p from al loc 0sx pl to 560 f well ation APPRoX APPROX APPROX APPROX Title OR STAT	d measured and tr BLM/BIA. Requ n or recompletion ns, including recl FT C/BP CMT D ID tree, able out oull out 12,950' ck casing Lug (50s: Lug from D'. Lhead 4' 92.0 94 Cheen and Cheen an	vio make to grav	ate JUL 1	arkers and zones. Ad within 30 days hall be filed once I the operator has NE DPS. 7' or d cut DC and t ECOVERY x above) 0'(BASE OI (ETNT. ( d on dry 5 20()2 ncy of the United	DE A SET CICR

OCP