

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
B-9312

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Sirgo-Collier, Inc. 3. Address of Operator P. O. Box 3531, Midland, Texas 79702 4. Location of well UNIT LETTER <u>D</u> , <u>100</u> FEET FROM THE <u>North</u> LINE AND <u>1210</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>25S</u> RANGE <u>38E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3137' GR 3148.5' KB	7. Unit Agreement Name West Dollarhide Queen Sand Unit 8. Farm or Lease Name 9. Well No. 117 10. Field and Pool, or Wildcat Dollarhide Queen 12. County Lea
---	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud, cement surface &amp; prod. casing</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-22-88 Spudded with 12-1/4" bit to TD of 417'. Ran 13 joints of 8-5/8" 24# casing to 414'. Cemented with 250 sx Class "C" with 2% CaCl2. PD 3:15 pm. Circulated 55 sx.

3-23-88 WOC 18 hours. Tested casing and rams to 800# for 30 minutes. Tested okay.

3-27-88 TD 3910'. Ran 110 joints of 5-1/2" 15.5# casing to 3910'. Cemented with 725 sx Western Light cement with 15# salt, 1/4# celoseal, tailed with 200 sx Class "C" with 2% CaCl2. PD 11:30 pm. Circulated 20 sx.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amey L. Whitley TITLE Agent DATE March 29, 1988

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE  DATE APR 7 1988

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAR 30 1988  
OCD  
HOBBS OFFICE