

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30483
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No. G-313726
7. Lease Name or Unit Agreement Name R.R. Sims TN
8. Well No. No. 1
9. Pool name or Wildcat North Teague Ellenburger

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. Name of Operator Texaco Producing Inc.
3. Address of Operator P.O. Box 728 Hobbs, NM 88240	4. Well Location Unit Letter N : 330 Feet From The South Line and 2308 Feet From The West Line Section 4 Township 23 South Range 37 East NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3317' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 8 3/4" hole to 8690'. TD @ 2:00 a.m. 12-18-88

12-20-88: Ran 46 jts 7" 26# L-80 LTAC CSG (1707') and 157 jts 7" 26# K-55 L74C CSG (6965') set @ 8690' w/ FC @ 8608' & DV Tool @ 6982.

Cement in 2 stages:

1st stage: Pump 495 sacks class 'H' cement w/ 1/2" Floccle 10% Salt 3/10% Halad-9 (15.7 ppg, 1.01 yield) open DV Tool. Circulate 154 sacks to surface.

2nd stage: Pump 555 sacks HLW 'H' w/ 1/2" Floccle (12.4 ppg, 1.97 yield) followed by 400 sacks 30/50 Poz 'H' w/ 3/10% Halad-9 1/2" Floccle. Close DV Tool circulate 60 sacks to surface.

12-22-88: Test 7" CSG w/ 1500 psi for 30 minutes. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE K.L. Johnson TITLE AREA SUPERINTENDENT DATE JAN 21 1989

TYPE OR PRINT NAME K.L. Johnson TELEPHONE NO. 505-394-2585

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JAN 25 1989

636 8 5 MAL

RECEIVED
JAN 24 1909
U.S. DEPT. OF AGRICULTURE
BUREAU OF PLANT INDUSTRY

RECEIVED
JAN 24 1909
U.S. DEPT. OF AGRICULTURE
BUREAU OF PLANT INDUSTRY