

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
50% OF PRODUCTIONS ON RE-
LEASE

Form approved
Budget Bureau No. 1004-313
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS, 11/89

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Chevron U.S.A. Inc.

3. ADDRESS OF OPERATOR

P.O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit A, 1310' FNL and 210' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, FT, OR, ETC.)

3288'

5. LEASE DESIGNATION AND SERIAL NO.

LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. E. LaMunyon

9. WELL NO.

50

10. FIELD AND POOL, OR WILDCAT

Teague/Rlinebry

11. SEC. T. R. M. OR BLK. AND
SURVEY OR AREA

Sec. 28, T23S, R37E

12. COUNTY OR PARISH 13. STATE

Lea

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PLUG OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

run CSG

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per-
tinent to this work.)

2/19/89 Spud 7 7/8" hole 2-19-89 at 2:30am. Drill and survey to 5278'. Circ.
and condition hole for Cores. Core #1 f/5278-5338. Core #2 f/5338-5398.
Ream f/5278-5398. Drlg to 5455'. Circ. for core #3. Core #3 f/5455-5492.
Core #4 f/5492-5499. Core #5 f/5499-5520' 5520-5526'. Core #6 f/5526-
5586'. Ream 132' to bottom. TD 7 7/8" hole at 9PM 3-5-89. Circulate.
Run OH logs. Run GR-CNL-LDT. GR-DLL-MSFL, GR-BHC-Sonic. RFT. Run 5 1/2"
15.5#, K-55, LT&C csg. Set at 5960'. FC at 5913'. Circ. cap. Cmt 1st stg
w/100sx C1 C. Tailed w/690sx C1 C. Bump plug w/1600psi. Plug down at 5:05PM.
Cmt 2nd stg w/870sx C1 C. Tailed w/175sx C1 C. Bumped plug w/2400psi.
Circ 45sx to surf. Set slips, cut off. NU tbg spool. Rig released at
4:30am. 3-8-89.

ACCEPTED FOR RECORD

MAR 24 1989

SJS

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Elmae

TITLE Technical Assistant

DATE 3-15-89

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE