Form 3160-5 (November 1983) (Formerly 9-331)	UNID STATES SUBMIT IN TRIPLICATE (Other Instructions on DEPARTMENT OF THE INTERIOR verse side)  BUREAU OF LAND MANAGEMENT	5. LEASE DESIGNATION AND SBEIAL NO. LC-064118
(Do not use this for	RY NOTICES AND REPORTS ON WELLS rm for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL 2. NAME OF OPERATOR	OTHER	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME
Arch Petroles 3. Address of OPERATOR	um Inc.	E.C. Hill "D" Federal 9. WELL NO.
10 Desta Dr 4. LOCATION OF WELL (Rep. See also space 17 below. At surface	, Suite 420 East, Midland, Texas 79705  ort location clearly and in accordance with any State requirements.  )	6 10. FIELD AND POOL, OR WILDCAT
	O FSL, Section 34, T-23-S, R-37-E	Teague Devonian 11. sec., t., E., M., OR BLE. AND SURVEY OR AREA  Sec 34, T23S, R37E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 18. STATE Lea New Mexic
6.	Check Appropriate Box To Indicate Nature of Notice, Report, o	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	MULTIPLE COMPLETE  ABANDON*  CHANGE PLANS  (Other)  (Nowe: Person res	ALTERING CABING ABANDON MENT®
On January 28 cemented with		at 1175'. Halliburton locele at 10 BPM at 250#.
On January 28 cemented with	Completed of Recompleted Operations (Clearly State all pertinent details, and give pertinent details a	at 1175'. Halliburton locele at 10 BPM at 250#. to drilling out, the uccessful water shut-off.
On January 28 cemented with	Completed operations (Clearly state all pertinent details, and give pertinent dewell is directionally drilled, give subsurface locations and measured and true version of the surface of the surface casing was set ated at the surface. WOC for 12 hours. Prior was tested to 1000# for 30 minutes indicating s	at 1175'. Halliburton locele at 10 BPM at 250#. to drilling out, the uccessful water shut-off.
On January 28 cemented with	Completion or Recompleted Operations (Clearly state all pertinent details, and give pertinent dewell is directionally drilled, give subsurface locations and measured and true versions as the surface with 2% CaCl and 1/4# per sx f ated at the surface. WOC for 12 hours. Prior was tested to 1000# for 30 minutes indicating s	at 1175'. Halliburton locele at 10 BPM at 250#. to drilling out, the uccessful water shut-off.
17. DESCRIBE PROPOSED OR C proposed work. If we nent to this work.)*  On January 28 cemented with 180 sx circul surface plug	Completed operations (Clearly state all pertinent details, and give pertinent dewell is directionally drilled, give subsurface locations and measured and true version of the surface of the surface casing was set ated at the surface. WOC for 12 hours. Prior was tested to 1000# for 30 minutes indicating s	at 1175'. Halliburton locele at 10 BPM at 250#. to drilling out, the uccessful water shut-off.