

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31199
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name B.F. HARRISON "B"
8. Well No. 3
9. Pool name or Wildcat <i>Harris League</i> FUSSELMAN

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Texaco Exploration and Production Inc.

3. Address of Operator
P. O. Box 730 Hobbs, NM 88240

4. Well Location
Unit Letter C : 340 Feet From The NORTH Line and 1700 Feet From The WEST Line
Section 9 Township 23-S Range 37-E NMPM LEA

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3314' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- MIRU wireline mast.
- Install 5000 psi lubricator w/greasehead packoff to tree. Test lubricator to 2500 psi.
- TIH w/1-11/16" Dyna-Cap perforating gun (strip gun) w/2 JSPF, 0 deg phasing decentralized and perforate the following Fusselman interval: 8828'-8846' (18', total of 36 holes).
- TOH w/gun. RD lubricator and mast.
- Acidize Fusselman perms 8786'-8848' (total of 82 holes) w/5000 gallons of 15% NEFE and 120 1.3 S.G. ball sealers at a maximum rate of 8 BPM and maximum pressure not to exceed 4500 psi. Flush w/55 bbls 2% KCL.
- Flow/swab back load. Put on test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Monte C. Duncan TITLE ENGINEER'S ASSISTANT DATE 11/20/92
TYPE OR PRINT NAME MONTE C. DUNCAN TELEPHONE NO. 393-7191

(This space for State Use)

Orig. Signed
Paul Kautz
Geologist

NOV 20 '92

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: