

# INSTRUCTIONS

This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions. Copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments listed on this form, see item 35.

If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State office for specific instructions.

Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. Item 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

| ARY OF POROUS ZONES: |       |        | 38. GEOLOGIC MARKERS                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                       |                                                                                          |                  |
|----------------------|-------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------|
| ATION                | TOP   | BOTTOM | DESCRIPTION, CONTENTS, ETC.                                                                                                                                                                                                                               | NAME                                                                                                                                                                                                                                                                  | MEAS. DEPTH                                                                              | TRUE VERT. DEPTH |
| ware                 | 4280' | 4300'  | 95% Sandstone, light gray to gray slightly shaly, slightly calcareous, slightly laminated with black shale, silty. 80% good to fair oil fluorecence, SL cut when crushed. 5% Shale, black silty. Bailed rainbow show of oil with trace odor of sweet gas/ | Top Rustler FM<br>Top Salado Salt<br>Top Castile FM<br>Top Uppermost<br>Salt in Castile FM<br>Top "M" Salt in<br>Castile FM<br>Base of "M" Salt<br>Top Lowermost<br>Salt<br>Base Lowermost<br>Salt<br>Top Lamar Shale<br>"Delaware Lime"<br>Top Delaware<br>Sandstone | 1003<br>1310<br>2315<br><br>2935<br><br>3585<br>3729<br><br>3830<br>4075<br>4175<br>4280 |                  |