


DRILLING CONTROL CONDITION IV-B-5000 PSI WP



DRILLING CONTROL

MATERIAL LIST - CONDITION IV - B

- | | |
|----------------------|--|
| A | Texaco Wellhead |
| B | 5000# W.P. drilling spool with a minimum 2" flanged outlet for kill line and 3" minimum flanged outlet for choke line. |
| C | 5000# W.P. Dual ram type preventer, hydraulic operated with 1" steel, 5000# W.P. control lines. |
| D | 5000# W.P. Annular preventer, hydraulic operated with 1" steel, 3000# W.P. control lines. |
| E | Rotating Head with fill up outlet and extended Blosie line. |
| 1,2,4,5, 8,10,11, 12 | 2" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 3 | 2" minimum 5000# W.P. back pressure valve. |
| 6,9 | 3" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 7 | 3" minimum 5000# W.P. flanged hydraulic valve |
| 15 | 1" minimum Schedule 160, Grade B, seamless line pipe |
| 16 | 2" minimum x 1" 5000# W.P. flanged cross |
| 11,14 | 2" minimum 5000# W.P. adjustable chokes with cartridge trim. |
| 17 | Pressure Test Gauge or equivalent (location in choke line optional). |
| 13 | 6" minimum 1000# hydraulic flanged valve. |
| 14 | 6" minimum steel line pipe. |
| 18 | 1" minimum 1000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |

