

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 2244

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sarah B No. 2

9. API Well No.

30-025-32052

10. Field and Pool, or Exploratory Area

Cline, Tubb

11. County or Parish, State

Lea County, New Mexico

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Samedan Oil Corporation

3. Address and Telephone No

10 Desta Drive, Suite 240 East, Midland, Texas 79705

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 1803' FWL, Sec. 12, T-23-S, R-37-E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Run casing string

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/28/93: Ran 21 jts 13-3/8" 48# H-40 ST&C casing, Texas Pattern shoe & insert float 1 jt up + 5 centralizers. Set at 925'. Cemented with 560 sx class "C" with 4% gel + 2% CaCl₂, wt 13.5 ppg, yield 1.72, 7 BPM @ 250#. Tail in with 200 sx class "C" with 2% CaCl₂, wt 14.8 ppg, yield 1.32, 7 BPM @ 240#. Circulate 250 sx to surface. Bump plug with 330# at 5:00 PM.

7/12/93: Ran FS + 1 jt 5-1/2" 17# K-55 LT&C casing + FC + 150 jts 5-1/2" 17# K-55 LT&C casing, set at 6250'. Ran 10 centralizers. Cemented with 900 sx class "C" with 16% gel, 5# salt, 1/4# flocele, 4/10% CFR3. Tail in with 250 sx class "C". Plug down at 6:50 PM. 1800 psi, float held OK. Cement did not circulate. Ran temperature survey. TOC at 1100'.

14. I hereby certify that the foregoing is true and correct

Signed Judy Shronchinsky

Title Division Production Clerk

Date 8-2-93

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

J. Lara
25 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side