N.M. Oil Cons. Div 5n

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

P.O. Box 1980 Hobbs, NM 88241

FORM APPROVED

Budget	Bure	eau l	No. 1	004-0	135
Evn	irae.	Mar	ch 3	1 100	2

5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS LC-030174B Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Alottee or Tribe Name Use "APPLICATION FOR PERMIT --" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE OIL WELL 8. Well Name and Number 1. Type of Well: **◆** OTHER RHODES NCT COOP FED. COM-1 2. Name of Operator **TEXACO EXPLORATION & PRODUCTION INC.** 2 3. Address and Telephone No. 205 E. Bender, HOBBS, NM 88240 9. API Well No. 397-0432 30 025 32096 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, Exploaratory Area : 2310 Feet From The N Line and 2310 Feet From The RHODES YATES SEVEN RIVERS 11. County or Parish, State Line Section 27 Township 26S Range 37E Lea , New Mexico 12 Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** Notice of Intent Plugging Back Non-Routine Fracturing Subsequent Report Casing Repair Water Shut-Off Atlering Casing Conversion to Injection Final Abandonment Notice OTHER: ADD YATES PAY & ACIDIZE Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work,)*. 1)RUPU. Pull and inspect rods, Install BOP, 6-22-96 2) Tag fill and strap out of hole, 6-23-96 3)RU Sclumberger, run RST log. 6-24-96. 4)MIRU perforators. Perforate the Yates 2 JSPF, 22-.45" holes, 4" casing gun over the following intervals 3159'- 3170'(new perfs) total perfs (3159'-3230'). Set RBP @ 3250' & Packer @ 3190', Dowell acidized lower Yates perfs 3208'-3230' w/1500 gas 15% NEFE. Shut-in due to storm 6-26-96. 5)Reset RBP @ 3190' & PKR @ 3098'. Dowell acidized Upper Yates perfs 3159'-3170' w/3000 gals 15% NEFE. Release PKR & RBP & POH. 6-27-96 6)TIH w/ tubing/anchor/GA. SET SN AT 3300'. RIH w/ rods and pump. RD 6-28-96. 7)Put on test 6-29-96 thru 7-16-96. 8)OPT 14 bo. 57 bw. 2 mcf. **FINAL REPORT** BLM 14. I hereby certify that the forego **Engineering Assistant SIGNATURE** DATE Paula S. Ives TYPE OR PRINT NAME (This space for Federal or State office use) **APPROVED BY** CONDITIONS OF APPROVAL, IF ANY:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or

representations as to any matter within its jurisdiction.

