

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. NM 68084
2. Name of Operator Enron Oil & Gas Company	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. P. O. Box 2267, Midland, Texas 79702	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 660' FNL & 1980' FWL Sec 7, T24S, R32E	8. Well Name and No. Mesa Verde 7 Federal #2
	9. API Well No. 30 025 32399
	10. Field and Pool, or Exploratory Area Wildcat Delaware
	11. County or Parish, State Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other <u>Csg test & cmt job</u>
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-4-94 - Ran 10 jts 8-5/8" 32# S-80 ST&C & 93 jts 8-5/8" 32# K-55 ST&C casing set at 4470'.

Cemented with 1075 sacks PSL Type C (65:35:6) + 1/2#/sx cello-seal + 10% Salt; 12.7 ppg, 2.04 cuft/sx, 390 bbls slurry. And 200 sx Type C + 1% CaCl; 14.8 ppg, 1.33 cuft/sx, 47 bbls slurry. Reciprocated pipe while circulating 150% capacity of csg; reciprocated until tail reached shoe. Circulated 190 sacks cement.

WOC - 24 hours

30 minutes pressure tested to 1000 psi, OK.

14. I hereby certify that the foregoing is true and correct

Signed Betty Gildon Title Regulatory Analyst

Date 9/6/94

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: