

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III


1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30 025 32500
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil / Gas Lease	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG													
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____						7. Lease Name or Unit Agreement Name HARRISON, B. F. 'C'							
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER _____													
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.						8. Well No. 3							
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240						9. Pool Name or Wildcat North Teague Tubb Associated							
4. Well Location Unit Letter <u>L</u> : <u>1980</u> Feet From The <u>SOUTH</u> Line and <u>925</u> Feet From The <u>WEST</u> Line Section <u>9</u> Township <u>23-S</u> Range <u>37-E</u> NMPM <u>LEA</u> COUNTY													
10. Date Spudded 8/19/94		11. Date T.D. Reached 9/1/94		12. Date Compl. (Ready to Prod.) 12/23/94		13. Elevations (DF & RKB, RT, GR, etc.) 3319'-GR, 3331'-KB		14. Elev. Csghead					
15. Total Depth 7250'		16. Plug Back T.D. 6423'		17. If Mult. Compl. How Many Zones? 1		18. Intervals Drilled By Rotary Tools 0' - 7250'		Cable Tools					
19. Producing Interval(s), of this completion - Top, Bottom, Name 6115'-6288', Tubb Associated								20. Was Directional Survey Made YES					
21. Type Electric and Other Logs Run GR-DLL-MSFL-FWS, GR-CSNG-SDL-DSN								22. Was Well Cored NO					
23. CASING RECORD (Report all Strings set in well)													
CASING SIZE		WEIGHT LB/FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD		AMOUNT PULLED			
9 5/8		36#		1180'		12 1/4		550					
7		26# & 23#		7250'		8 3/4		4100					
24. LINER RECORD										25. TUBING RECORD			
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE	DEPTH SET	PACKER SET	
NONE										2-3/8"	6037'	NONE	
26. Perforation record (interval, size, and number) 6115'-6268', 2 JSPF, 104 HOLES										27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.			
										DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED	
										6115'-6268'		550g 15% NEFE + 3000g 15% HCL	
												56000g fluid + 190000# 20/40 sand.	
28. PRODUCTION													
Date First Production 12/21/94		Production Method (Flowing, gas lift, pumping - size and type pump) 2 x 1-1/2" x 22' pump						Well Status (Prod. or Shut-in) producing					
Date of Test 12/28/94		Hours tested 24		Choke Size		Prod'n For Test Period		Oil - Bbl. 23		Gas - MCF 95		Water - Bbl. 62	Gas - Oil Ratio 4130
Flow Tubing Press. 50 psi		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl. 23		Gas - MCF 95		Water - Bbl. 62		Oil Gravity - API -(Corr.) 41.8	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD										Test Witnessed By D. F. Sullivan			
30. List Attachments Deviation Survey													
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief													
SIGNATURE 				TITLE Engineering Assistant				DATE 2/3/95					
TYPE OR PRINT NAME Darren J. Carriger								Telephone No. 397-0426					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy	1092'	T. Canyon	T. Ojo Alamo	T. Penn "B"	
T. Salt	1190'	T. Strawn	T. Kirtland-Fruitland	T. Penn "C"	
B. Salt	2462'	T. Atoka	T. Pictured Cliffs	T. Penn "D"	
T. Yates	2605'	T. Miss	T. Cliff House	T. Leadville	
T. 7 Rivers	2959'	T. Devonian	T. Menefee	T. Madison	
T. Queen	3328'	T. Silurian	T. Point Lookout	T. Elbert	
T. Grayburg	3669'	T. Montoya	T. Mancos	T. McCracken	
T. San Andres	4018'	T. Simpson	T. Gallup	T. Ignacio Otzte	
T. Glorieta	5056'	T. McKee	T. Base Greenhorn	T. Granite	
T. Paddock	5260'	T. Ellenburger	T. Dakota	T.	
T. Blinebry	5589'	T. Gr. Wash	T. Morrison	T.	
T. Tubb	6112'	T. Delaware Sand	T. Todilto	T.	
T. Drinkard	6346'	T. Bone Springs	T. Entrada	T.	
T. Abo	6639	T.	T. Wingate	T.	
T. Wolfcamp		T.	T. Chinle	T.	
T. Penn		T.	T. Permian	T.	
T. Cisco (Bough C)		T.	T. Penn "A"	T.	

OIL OR GAS SANDS OR ZONES

No. 1, from 6112' to 6346'	No. 3, from to
No. 2, from to	No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1092	1092	REDBEDS	6639	7250TD	611	DOL., ANHYD., SHALE
1092	1190	98	ANHYD.				
1190	2462	1272	SALT, ANHYD., SHALE				
2462	2605	143	ANHYD., SALT, DOL.				
2605	2959	354	SNDSTNE., ANHYD., DOL.				
2959	3328	369	DOL., SNDSTNE.				
3328	3669	341	SNDSTNE., DOL.				
3669	4018	349	DOL., SNDSTNE				
4018	5056	1038	DOL., ANHYD.				
5056	5260	204	DOL.				
5260	5589	329	DOL., ANHYD.				
5589	6112	523	DOL., ANHYD.				
6112	6346	234	SNDSTNE., DOL.				
6346	6639	293	DOL., ANHYD.				