

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30 025 32682
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	G 38047

WELL COMPLETION OR RECOMPLETION REPORT AND LOG											
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐											
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐											
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.											
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240											
4. Well Location Unit Letter <u>O</u> <u>660</u> Feet From The <u>SOUTH</u> Line and <u>1976</u> Feet From The <u>EAST</u> Line Section <u>2</u> Township <u>24-S</u> Range <u>36-E</u> NMPM <u>LEA</u> COUNTY											
10. Date Spudded 11/4/94		11. Date T.D. Reached 11/13/94		12. Date Compl. (Ready to Prod.) 2/5/95		13. Elevations (DF & RKB, RT, GR, etc.) 3357-GR, 3369-KB			14. Elev. Csghead		
15. Total Depth 3880'		16. Plug Back T.D. 3840'		17. If Mult. Compl. How Many Zones? 1		18. Intervals Drilled By 0' - 3880'		Rotary Tools		Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 3060' - 3084', Yates; 3255'-3494', Seven Rivers										20. Was Directional Survey Made Yes	
21. Type Electric and Other Logs Run GR-DLL-MSFL, GR-DSM-SDL, CAL, GR-BHC-SONIC										22. Was Well Cored NO	
23. CASING RECORD (Report all Strings set in well)											
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD		AMOUNT PULLED	
8 5/8		24#		430'		11		250 SACKS			
5 1/5		15.5#		3880'		7 7/8		970 SACKS			
24. LINER RECORD											
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN			
NONE											
25. TUBING RECORD											
SIZE		DEPTH SET		PACKER SET							
2-3/8"		3546'		NONE							
26. Perforation record (interval, size, and number) 3060'-3084', 96 HOLES 3255'-3494', 72 HOLES											
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.											
DEPTH INTERVAL						AMOUNT AND KIND MATERIAL USED					
3060'-3084'						37000G 40# GEL+13800# 12/20 SAND					
3255'-3494'						2000G NEFE+37000G 40# GEL+138000#12					
						12/20 SAND					
28. PRODUCTION											
Date First Production 12/20/94		Production Method (Flowing, gas lift, pumping - size and type pump) PUMP (2.5" X 1.25 X 12")						Well Status (Prod. or Shut-in) PRODUCING			
Date of Test 2/13/95		Hours tested 24		Choke Size 28/64		Prod'n For Test Period		Oil - Bbl. 0		Gas - MCF 196	
Water - Bbl. 8		Gas - Oil Ratio		Flow Tubing Press. 37		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl. 0	
Gas - MCF 196		Water - Bbl. 8		Oil Gravity - API -(Corr.)							
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD										Test Witnessed By B. D. WARD	
30. List Attachments DEVIATION SURVEY											
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.											
SIGNATURE <u>Darrell J. Carriger</u>						TITLE Engineering Assistant		DATE 5/2/95			
TYPE OR PRINT NAME Darrell J. Carriger						Telephone No.		397-0426			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1253	T. Canyon
T. Salt	1410	T. Strawn
B. Salt	2828	T. Atoka
T. Yates	2986	T. Miss
T. 7 Rivers	3204	T. Devonian
T. Queen	3600	T. Silurian
T. Grayburg	3800-TD	T. Montoya
T. San Andres		T. Simpson
T. Glorieta		T. McKee
T. Paddock		T. Ellenburger
T. Blinebry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkard		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 2986 to 3204
 No. 2, from 3204 to 3600

No. 3, from to
 No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet
 No. 2, from to feet
 No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1253	1253	REDBEDS				
1253	1410	157	ANHYD.				
1410	2828	1418	SALT, ANHYD., SHALE				
2828	2986	158	ANHID., SALT, DOL.				
2986	3204	218	SNDSTNE., ANHYD., DOL.				
3204	3600	396	DOL., SNDSTNE.				
3600	3800	200	SNDSTNE., DOL.				
3800	3880TD	80	DOL., SNDSTNE				