Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR

٨.	M	-	'i (CONS	COMMISSION
ø	(3)	٨.	έ¥	1000	אַרָּהַנְיוּשׁוּיִיבּבּ

Č

FORM APPROVED (June 1990) NEW MEXIGG B880301004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-14164 SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Gias Well Other 8. Well Name and No. 2. Name of Operator Antelope 5 Federal No. 1 Pogo Producing Company 9. API Well No. 3. Address and Telephone No. 30-025-32734 P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Wildcat 1980' FNL & 1650' FWL, Section 5, T24S, R35E 11. County or Parish, State Lea County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent A pandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud & Surface Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU Nabors #347. Spud @ 0600 hrs CST 11/29/94. Drilled 17-1/2" hole to 538'. TD reached 1315 hrs CST 11/29/94. Ran 12 jts 13-3/8" 54.5# J-55 ST&C casing. TPGS @ 538'. IFV @ 490'. Howco cmt'd casing w/ 500 sxs Halliburton Lite @ 12.8 ppg followed by 200 sxs Class "C" + 2% CaCl₂ @ 14.8 ppg. Plug down @ 1845 hrs CST 11/29/94. Recovered 200 sx excess cement. WOC 15 hrs. Cement has a compressive strength over 500 psi after 8 hours. Make cut-off. Weld on wellhead and test to 500 psi. NU BOP's and test to 1500 psi.

		62S
14. I hereby certify that the foregoing is true and correct Signed	Tide Senior Operations Engineer	Date Jan. 4, 1995
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction