

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-32900
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG							
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____				7. Lease Name or Unit Agreement Name G. W. SIMS			
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER _____							
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.				8. Well No. 4			
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240				9. Pool Name or Wildcat North Teague(Drinkard-Abo,Lower Pad.-Blin.Ass.)			
4. Well Location Unit Letter G : 1980 Feet From The NORTH Line and 2310 Feet From The EAST Line Section 9 Township 23-S Range 37-E NMPM LEA COUNTY							
10. Date Spudded 4/15/95		11. Date T.D. Reached 4/25/95		12. Date Compl. (Ready to Prod.) 5/11/95		13. Elevations (DF & RKB, RT, GR, etc.) 3305' GR	
15. Total Depth 7250'		16. Plug Back T.D. 7200'		17. If Mult. Compl. How Many Zones?		18. Intervals Drilled By 0'-7250'	
19. Producing Interval(s), of this completion - Top, Bottom, Name 5720-5952;6610-6625;6912-6927;6851-7142						20. Was Directional Survey Made NO	
21. Type Electric and Other Logs Run GR-DLL-MSFL-BHCS-CAL; CSNG-CNL-LDT-CAL; GR-CNL						22. Was Well Cored NO	
23. CASING RECORD (Report all Strings set in well)							
CASING SIZE		WEIGHT LB/FT.		DEPTH SET		HOLE SIZE	
9-5/8"		36#		1190'		12 1/4	
7"		23,26, 32#		7250'		8 3/4	
24. LINER RECORD							
SIZE		TOP		BOTTOM		SACKS CEMENT	
NONE							
25. TUBING RECORD							
SIZE		DEPTH SET		PACKER SET			
2-3/8"		6811'		6004'			
2-1/16"		5700'					
26. Perforation record (interval, size, and number)							
5720-5952, 2 JSPF, 164 HOLES (BLNBRY) 6610-6625, 6 JSPF, 90 HOLES (DRNKRD) 6851-7142, 2 JSPF, (ABO) 6912-6927, 6 JSPF, 90 HOLES (ABO) North Teague Lower Paddock-Blinebry Asso. pool is dually completed with the North Teague Drinkard-Abo Pool.							
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.							
DEPTH INTERVAL				AMOUNT AND KIND MATERIAL USED			
6912-6927				AF/17680GW/1# PPG PROPNET			
6851-7142				AF/30000G55Q,47000G30#LFP,300BS			
6610-6625				AF/5000G40#5000G50#19556#20/40,30000G55Q,47000G30#LFP,180BS			
				AF/2000G15%,250 BS F/54000G40#,180000# 16/30			
28. PRODUCTION 5720-5952							
Date First Production 5/12/95		Production Method (Flowing, gas lift, pumping - size and type pump) FLOWING (BLINEBRY - DRINKARD ABO)					Well Status (Prod. or Shut-in) PRODUCING
Date of Test 7/29/95		Hours tested 24		Choke Size 11/64-20/64		Prod'n For Test Period	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.	
						Gas - MCF	
						Water - Bbl.	
						Oil Gravity - API -(Corr.) 42.2	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						Test Witnessed By D. E. WELBORN	
30. List Attachments DEVIATION SURVEY							
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.							
SIGNATURE <i>M. Angie Davila</i>				TITLE Clerk		DATE 8/11/95	
TYPE OR PRINT NAME M. Angie Davila				Telephone No. 397-0443			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1123'	T. Canyon
T. Salt	1263'	T. Strawn
B. Salt	2463'	T. Atoka
T. Yates	2602'	T. Miss
T. 7 Rivers	2821'	T. Devonian
T. Queen	3324'	T. Silurian
T. Grayburg	3672'	T. Montoya
T. San Andres	4024'	T. Simpson
T. Glorieta	5072'	T. McKee
T. Paddock	5268'	T. Ellenburger
T. Blinebry	5594'	T. Gr. Wash
T. Tubb	6114'	T. Delaware Sand
T. Drinkard	6304'	T. Bone Springs
T. Abo	6626'	T.
T. Wolfcamp	7250' TD	T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	5720	to	5952
No. 2, from	6610	to	6625

No. 3, from	6851	to	7142
No. 4, from	6912	to	6927

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1123'	1123'	REDBEDS				
1123'	1263'	140'	ANHYDRITE				
1263'	2463'	1200'	SALT, ANHY, SHALE				
2463'	2602'	139'	ANHY, SALT, DOLOMITE				
2602'	2821'	219'	SNDSTONE, ANHY, DOLO				
2821'	3324'	503'	DOLO, SANDSTONE				
3324'	3672'	348'	SANDSTONE, DOLO				
3672'	4024'	352'	DOLO, SANDSTONE				
4024'	5072'	1048'	DOLO, ANHY				
5072'	5268'	196'	DOLOMITE				
5268'	5594'	326'	DOLO, ANHY				
5594'	6114'	520'	DOLO, ANHY				
6114'	6304'	190'	SNDSTONE, DOLO				
6304'	6626'	322'	DOLO, ANHY				
6626'	7250'	624'	DOLO, ANHY, SHALE				