

APPLICATION TO DRILL

Plains Petroleum Operating Company

E. C. Hill 'B' Federal #13

Lea County, New Mexico

Lease No. 064118

March 28, 1995

Page 4

4. MUD DETAIL

<u>DEPTH</u>	<u>PROPERTIES</u>	<u>TREATMENT</u>
0 - 350'	Weight: 8.7 - 9.4 Viscosity: 33 - 35 Solids: <4.	Spud Mud: Fresh water gel with sufficient to viscosity to clean hole.
350' - 3000'	Weight: 10.0 - 10.2 Viscosity: 26 - 28 Solids: < 1.0	Drill out from surface csg with brine water
3000' - 9850'	Weight: 8.6 - 9.2 Viscosity: 28 - 35 Solids < 1.0 WL 7 - 10	Drill out from intermediate casing with fresh water mud

5. PRESSURE CONTROL EQUIPMENT (BOPE) DETAIL

13-5/8" API Shaffer 3000# series 600 dual hydraulic preventers adapted for the drilling contractors 4-1/2" drill pipe. The BOPS will be tested after they are installed on the surface casing, prior to drilling out, and each time they are removed or rearranged on the wellhead. See Exhibit A.

6. TESTING AND LOGGING PROGRAMS

TESTING

Drill stem tests may be performed to quantify and identify prospective producing horizons as drilling progresses. Production testing will be commenced after the well is drilled and casing has been set and cemented.

LOGGING

At TD, the following open hole well logs will be run: **GR-CNL-CDL-DLL-MLL**

RECEIVED

1985
OFFICE