N. M. OIL CONS. COMMISSION P. O. BOX 1980

9. API Well No.

30-025-33136

Conversion to Injection

Dispose Water Note: Report results of multiple completion on Wel on or Recompletion Report and Log form.)

HOBBS, NEW MEXICO 98246 FORM APPROVED **UNITED STATES** Form 3160-5 Budget Bureau No. 1004-0135 DEPARTMENT OF THE INTERIOR (June 1990) **BUREAU OF LAND MANAGEMENT** Expires: March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS LC-030187 Do not use this form for proposals to drill or deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT-" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of well 8. Well Name and No. Other X Oil Gas C. E. LAMUNYON #53

10 Desta Dr. Suite 420E, Midland, TX	10. Field and Pool, or Exploratory Area		
Location of Well (Footage, Sec., T., R., M., or Survey Description)		TEAGUE BLINEBRY	
		11. County or Parish, State	
1300' FSL, 330' FWL, SEC. 22, T23S, R37E		LEA COUNTY, NM	
CHECK APPROPRIATE BOX	((S) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent	Abandonment	Change of Plans	
	Recompletion	New Construction	
X Subsequent Report	Plugging Back	Non-Routine Fracturing	
	Casing Repair	Water Shut-Off	

Altering Casing

Other Spud, Run & Cement Casing

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU Peterson Drilling, spud 12-1/4" hole at 6:30 pm, 10/23/95.

Final Abandonment Notice

TD 12-1/4" hole at 1075'. Ran 24 joints 8-5/8", 32#, J-55, ST&C casing. Set at 1075'. Cement with 400 sx. Halliburton Lite, tail in with 200 sx. Class 'C' neat. Plug down at 6:00 pm, 10/12/95. Circ. 103 sx. to surface. WOC 12 hrs. Pressure test surface casing to 1200 psi. OK.

Drill out csg. shoe and drill 7-7/8" hole. Drill and survey to 6000'. TD 7-7/8" @ 2:00 pm, 11/2/95. Ran OH logs. Ran 134 jts. 5-1/2", 15.5#, J-55, LT&C csg. Set at 6000'. Cement with 1156 sx. lead cement, tail in with 500 sx. 50/50 pozmix. Dispace plug to float collar w/ 1500 psi, did not bump. Plug down at 5:30 pm, 11/3/95. Circulate 145 sx. cement to surface. Set slips, cut off csg. NU tbg. head. WOC 24 hrs.

Released rig 11/3/95.

2. Name of Operator

3. Address and Telephone No.

ARCH PETROLEUM, INC.

HOBBS INSPECTION OFFICE ACCEPTED FOR RECORD DATE 11-13-55 SIGNATURE URING

14. I hereby certify that the forgoing is true and correct Signed School School	Title	PRODUCTION ANALYST	Date	11/9/95
(This space for Federal or State office use)				
Approved by Conditions of approval, if any:	Title		Date	