m 3150.5 - WED	ITED STATES	FORM APP	ROVED		
In 1990		Rudget Russey Me			
196 BUREALLOE	LAND MANAGEMENT	8824Qxpires: March			
		5. Lease Designation	and Serial No.		
10,22		10-	050107B		
Form 3160-5 CEIVED UNITED STATES BUREAU OF LAND MANAGEMENT OF THE INTERIOR BBS, NEW MEXICO UNITED STATES P.O. BUK 1880 BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS		6. If Indian, Allottee or Tribe Name			
bo not use this form for proposals to drill or to dee	non or reentry to a different recepuoir				
Use "APPLICATION FOR PERMIT " for					
		7. If Unit or CA, Agre	ement Designatio	n	
SUBMIT IN	TRIPLICATE				
Type of Well					
X Oil Gas Temporarily Abandoned					
Well Well Other		8. Well Name and No. Wills Federal			
		WEI	LL # 3		
MR DRILLING COMPANY Address and Telephone No.		9. API Well No.			
P.O. BOX 687, MONAHANS, TEXAS 79756 (915) 9	43-2501				
Leasting of Mall (Footness Cop. T. D. M. or Curry Department		10. Field and Pool, c	x Exploratory Are	a	
Location of Well (Footage, Sec., T., R., M., or Survey Description)		Rhodes, Yates			
SURFACE: 330' FNL & 2970' FEL of Section 34, T-26S, R-37E TD: Same		11. County or Parish, State LEA, NM			
CHECK APPROPRIATE BOX(s) TO INDIC	ATE NATURE OF NOTICE, REPORT, OR	OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION	•••••••••••••••••••••••••••••••••••••••			
Notice of Intent	Abandonment P&A	Change of Plans	5		
	Recompletion	New Constructio	n		
X Subsequent Report	Plugging Back	Non-Routine Fra	icturing		
	Casing Repair	Water Shut-Off			
Final Abandonment Notice	Altering Casing	Conversion to In	jection		
	X Other	Dispose Water			
	X Other Spud & Set Surface Casing	Oispose Water (Note: Report results of mult	tiple completion on Wel		
	Spud & Set Surface Casing	(Note: Report results of mult Completion or Recompletion	Report and Log form }		
Describe Proposed or Completed Operations (Clearly state all pertin directionally drilled, give subsurface locations and measured and	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s	(Note: Report results of mult Completion or Recompletion Starting any proposed work	Report and Log form }		
	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s	(Note: Report results of mult Completion or Recompletion Starting any proposed work	Report and Log form }		
	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s	(Note: Report results of mult Completion or Recompletion Starting any proposed work	Report and Log form }	.	
	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s	(Note: Report results of mult Completion or Recompletion Starting any proposed work	Report and Log form }		
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well.	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo	(Note Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is		
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is h0e, 54 jts. K-l	55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hiled with 150 (55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hiled with 150 (55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hiled with 150 (55 28# 8-5	
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hiled with 150 s	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hiled with 150 s	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- tiled with 150 s HOBE	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- alled with 150 s HOBBS, HOBBS,	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- tiled with 150 s HOBE	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- hoe, 54 jts. K- HOBBS, HO HOBBS, HO HOBBS, HO HOBBS, HO	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- hoe, 54 jts. K- HOBBS, HO HOBBS, HO HOBBS, HO HOBBS, HO	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE SIGNATURE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- alled with 150 s HOBBS, HOBBS,	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE SIGNATURE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco F d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- hoe, 54 jts. K- HOBBS, HO HOBBS, HO HOBBS, HO HOBBS, HO	55 28# 8-5	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FC DATE JATE SIGNATURE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P ed 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed worr ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- alled with 150 s HOBBS, NE HOBBS, NE HOBBS, NE	55 28# 8-5/ sx Halco P Mar 1 10 27 AH 95	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FO DATE	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of a true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P d 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed wort ork.)*	Report and Log form) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- hoe, 54 jts. K- HOBBS, HO HOBBS, HO HOBBS, HO HOBBS, HO	55 28# 8-5/ sx Halco P Mar 1 10 27 AH 95	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FO DATE JATE SIGNATURE I hereby certify that the foregoing is true and correct Signed MMM-C. MMM Title	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P ed 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed worr ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- alled with 150 s HOBBS, NE HOBBS, NE HOBBS, NE	55 28# 8-5/ sx Halco P Mar 1 10 27 AH 95	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FO DATE JATE SIGNATURE I hereby certify that the foregoing is true and correct Signed MMM-C. May Title (This space to Federal or State office use)	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P ed 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed worr ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- alled with 150 s HOBBS, NE HOBBS, NE HOBBS, NE	55 28# 8-5/ sx Halco P Mar 1 10 27 AH 95	8CZ.
directionally drilled, give subsurface locations and measured and 2-28-96 Spudded well. 3-01-96 Drilled to a total depth of 1285'. Run Toto 15 jts. K-55 24#/ft 8-5/8". RU Halliburton Plug down at 2:15 am 3-01-96. Circulate HOBBS INSPEC ACCEPTED FO DATE JATE SIGNATURE I hereby certify that the foregoing is true and correct Signed MMM-C. MMM Title	Spud & Set Surface Casing ent details, and give pertinent dates, including estimated date of s true vertical depths for all markers and zones pertinent to this wo to and POOH w/ drill string. RU casing crew and run and circulate 1-1/4 hrs. Cement with 520 sx Halco P ed 100 sx to pit. W.O.C.	(Note: Report results of mult Completion or Recompletion starting any proposed worr ork.)*	Report and Log form.) k. If well is hoe, 54 jts. K- hoe, 54 jts. K- alled with 150 s HOBBS, NE HOBBS, NE HOBBS, NE	55 28# 8-5/ sx Halco P Mar 1 10 27 AH 95	

*See Instruction on Reverse Side