Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-57274 Rd_{ij}^{-} SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well X Oil Well 8. Well Name and No. Gas Well U Other Haracz AMO Federal #7 2. Name of Operator (505) 748-1471)9. API Well No. YATES PETROLEUM CORPORATION 30-025-33345 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Wildcat Bone Springs 11. County or Parish, State 1650' FNL & 2310' FWL of Section 19-T24S-R32E (Unit F, SENW) Lea Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment **New Construction** Recompletion Non-Routine Fracturing X Subsequent Report Plugging Back Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice X Other Spud, resume drilling, Dispose Water (Note: Report results of multiple completion on Well surface casing & cement Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded a 26" hole with rat hole machine at 10:30 AM 3-21-96. Set 36' of 20" conductor pipe. Cemented to surface. NOTE: Notified Andrea with BLM-Hobbs of spud. Resumed drilling a 17-1/2" hole with rotary tools at 3:15 PM 3-23-96. TD 766'. Reached TD at 8:00 PM 3-24-96. Ran 17 joints of 13-3/8" 54.5# J-55 8rd ST&C (770.85') of casing set at 766'. 1-Texas Pattern notched guide shoe set at 766'. Insert float set at 726'. Cemented with 100 sacks "H", 8% A-10, 10#/sack gilsonite, 1/2#/sack celloseal and 1% CaCl2 (yield 1.58, weight 14.2) and 425 sacks BJ Lite C, 1/4#/sack celloseal and 2% CaCl2 (yield 1.99, weight 12.4). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 5:00 AM 3-25-96. Bumped plug to 600 psi, OK. Circulated 335 sacks. WOC. Nippled up and tested to 1000# for 30 minutes, OK. Drilled out at 12:45 AM 3-26-96. WOC 19 hours and 45 minutes. Reduced hole to 11". Resumed drilling. 14. I hereby certify that the foregoing is true and correct Date March 28, 1996 Production Clerk Foderal or State office use) (This space for Title Imos

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, lictitious or fraudulent statements or representations as to any matter within its jurisdiction.